



Main

Range	ComPact
Product name	INSJ400
Switch-disconnector name	Interpact INSJ400
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	250 A AC 50/60 Hz 600 V
[Uimp] rated impulse withstand voltage	8 kV
[Icm] rated short-circuit making capacity	100 KA protected by circuit breaker NSJ400 - 400A 480 V AC at 50/60 Hz 150 KA protected by circuit breaker NSJ400 - 400A 240 V AC at 50/60 Hz 20 KA protected by any protection device 600 V AC at 50/60 Hz 25 KA protected by circuit breaker NSJ400 - 400A 600 V AC at 50/60 Hz 50 kA with class T or RK fuses 400 A 600 V AC at 50/60 Hz
[Ue] rated operational voltage	600 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Plate
Upside connection	Front
Downside connection	Rear Front
Mechanical durability	5000 cycles conforming to UL 489
Electrical durability	1000 cycles full load
Height	205 mm
Width	185 mm
Depth	130 mm
Net weight	4.6 kg

Environment






Standards	UL 489 CSA C22.2 No 5.2
-----------	----------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	18 cm
Package 1 Length	20.7 cm
Package 1 Weight	5.068 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	10.577 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------