
Terminal rails

AK 3/14 PE



AK 3/14 PE

Terminal rails

Productnumber: 73485001
Dimensions: 29 x 273 x 49 mm

Terminal rail, as additional terminals or for replacement for installation in AK 24 and AK36 (since 10/2025)

Base carrier with PE terminal rail with 3 screw terminals 2.5-16 mm² and 14 push-in terminals 0.75-4mm², suitable for mounting of 2 N-modules

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Number of poles:	1
shockproof:	Yes
Connection 1: Connection type:	Screws
Connection 1: Strip length:	13 mm
Connection 1: Clamping points per pole:	3
Connection 1: Suitable for Cu conductors:	1
Connection 1: Suitable for Al conductors:	1
Connection 1: Connectable conductor cross-section, fine-wire without ferrule (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, fine-wire without ferrule (max):	16 mm²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max):	16 mm²
Connection 1: Connectable conductor cross-section, single-wire (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	16 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	2.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	16 mm²
Connection 2: Connection type:	Screwless
Connection 2: Stripping length:	12 mm
Connection 2: Clamping points per pole:	14
Connection 2: Suitable for Cu conductors:	1
Connection 2: Suitable for Al conductors:	1
Connection 2: Connectable conductor cross-section, fine-wire without ferrule (min):	0.75 mm²
Connection 2: Connectable conductor cross-section, fine-wire without ferrule (max):	4 mm²

electrical characteristics

Connection 2: Connectable conductor cross-section, fine-wire with ferrule (min):	0.75 mm²
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (max):	4 mm²
Connection 2: Connectable conductor cross-section, single-wire (min):	0.75 mm²
Connection 2: Connectable conductor cross-section, single-wire (max):	4 mm²
Connection 2: Connectable conductor cross-section, stranded (min):	0.75 mm²
Connection 2: Connectable conductor cross-section, stranded (max):	4 mm²

Dimensions

Width:	29 mm
Length:	273 mm
Height:	49 mm
Weight:	0.1077 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Connection 1: Tightening moment:	2 Nm

Sales Information

EAN:	4013902705047
ETIM Class:	EC001284
Custom tariff number:	85369010
Minimum order quantity:	1

Material

Insulating body material:	Thermoplastic

Accessories

73385201 - AK3 1/6/1 N - N-Module-Set