Small cable house junction box

SVi H 12R-g



SVi H 12R-g

Small cable house junction box

Productnumber: 59301301
Dimensions: 150 x 300 x 137 mm

Mains connection box, for 230 V alternating current mains (L-N-PE / L-PEN) according to VDE-AR-N 4100 (domestic junction box for single-phase connection), In=25 A, Imax=63 A, equipped with: 1 x NH00 fuse element, 1 x N-terminal, 1 x PE-terminal, 1 x PE-N jumper 10 mm², 1 x parking bay for 2 wire connection terminal supply cable: Box terminal (6 - 50 mm² CU, 10 - 50 mm² AL)
Connection terminals Outlet: Clamp connection (2x 2.5-50mm² CU)

Cover, grey

IP54 IK07 400V AC

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Protection class:	II
Type of protection:	IP54
UL Type Rating:	not specified

Dimensions

Width:	150 mm
Length:	300 mm
Height:	137 mm
Weight:	2.005 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Surface mounting
Impact strength:	IK07

Ambient conditions

Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902369898
ETIM Class:	EC000248
Custom tariff number:	85369095

Sales Information

Minimum order quantity:	1

Material

Base unit material:	Plastic

Certificates

Test mark:	VDE (DIN EN 61439-1/-2 (VDE 0660-600-1/-2))
Test mark:	VDE (DIN 0660-505)

Accessories

59341601 - PVK 416 - Tunnel terminal 1-pole, 4x16²

Cable gland

