
Channel installation box

KD 2 70/55 K3 gr



KD 2 70/55 K3 gr

Channel installation box

Productnumber: 38245501
Dimensions: 71 x 142 x 59 mm

Channel installation box, rated insulation voltage: 400V AC, certified by VDE (DIN EN 50085-1 (VDE 0604-1))

2-way, for installation in Kleinhuis wall trunking/device installation ducts

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V

Colours

Cover colour:	green

Dimensions

Width:	71 mm
Length:	142 mm
Height:	59 mm
Weight:	0.08 kg

Material characteristics

Halogen free:	no

Ambient conditions

max. relative humidity 25°C:	100 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	Indoors

Sales Information

EAN:	4013902030866
ETIM Class:	EC000073
Custom tariff number:	39269097
Minimum order quantity:	20

Material

Base unit material:	Polypropylene

Material

Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 50085-1 (VDE 0604-1))