2067 TORX® HF Screwdriver with holding function for electronic applications, TX 8 x 60 mm



EAN:	4013288108661	**Size:**	157x13x13 mm
Part number:	05118184001	**Weight:**	14 g
Article number:	2067 TORX® HF	**Country of origin:**	CZ
		Customs tariff number:	82054000

- Kraftform Micro TORX® HF screwdriver with holding function for recessed TORX® screws
- Multi-component Kraftform Micro handle with anti-roll feature and rotating cap
- The Wera Black Point tip offers an exact fit and optimum corrosion protection
- Holding function for TORX® screws, chrome-plated
- Take it easy tool finder: colour coding according to profile and size
- E.g. for electricians, opticians, precision mechanics, jewellers or IT hardware fitters

Premium Wera Micro screwdriver for precision mechanical couplings. With practical holding function: The clamping force resulting from the seating stress between the tip and the screw profile keeps the screws securely on the tool. By supporting the hand on the rotating cap, and due to the fast rotating zone below the rotating cap, lightning fast turning is possible. Time-consuming hand switching is eliminated. The power zone with integrated soft zones ensures the transmission of high tightening and loosening moments. Precision zone for correct rotation angles whilst adjusting. The Wera Black Point tip offers fitting accuracy and optimised corrosion protection. Take it easy tool finder with size stamping and colour coding by profile for quick and easy identification of the required tool.

TAKE IT EASY TOOL FINDER

FREE SPIN CAP

FAST SPINNING ZONE

POWER ZONE

PRECISION ZONE

HOLDING FUNCTION

BLACK POINT

ANTI ROLL-OFF

Web link
https://www.wera.de/en/05118184001

Wera - 2067 TORX® HF
05118184001 - 4013288108661

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de



Screwdriving jobs in electrical and precision engineering applications are often tedious and time-consuming. We learned from users what is important for them: working speeds, torque, precision - and we then focused particularly on these issues.

TORX® HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

Kraftform Micro handle




Multi-component screwdriver handle for ergonomic working.

The refined screwdriver for electronics technicians




The Kraftform Micro, with its three zones and their specific arrangement, satisfies these requirements perfectly. The free-turning cap that provides support for the hand works with these advantages, enabling quick and easy precision work.

The precision zone




The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.

The power zone



The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.

The fast-turning zone



The fast-turning zone just below the rotating cap allows rapid spinning.

Take it easy Tool Finder



Screwdrivers with Take it easy tool finder: colour coding according to profile and size stamp.

Web link
https://www.wera.de/en/05118184001

Wera - 2067 TORX® HF
05118184001 - 4013288108661

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

		mm	mm	mm	inch
05118180001	TX 4	40	97	2.5	1 9/16"
05118181001	TX 5	40	97	3.0	1 9/16"
05118182001	TX 6	40	97	3.0	1 9/16"
05118183001	TX 7	60	97	3.0	2 3/8"
05118184001	**TX 8**	**60**	**97**	**3.0**	**2 3/8"**
05118185001	TX 9	60	97	4.0	2 3/8"
05118186001	TX 10	60	97	4.0	2 3/8"

Web link
https://www.wera.de/en/05118184001

Wera - 2067 TORX® HF
05118184001 - 4013288108661

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de