
Junction box

Mini 25 SB-L



Mini 25 SB-L

Junction box

Productnumber: 31070801
Dimensions: 89 x 43 x 38 mm

Junction box, protection class IP55, nominal cross-section 2.5 mm², Ui=400 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), self-sealing insertion membranes, sealing range 8,2 - 12,5 mm, (2 rear, 10 side), external fixing lugs, for standard indoor installations

red, without terminals

IP55 | 2,5² | IK07 | 400V AC

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	2,5 mm²
Protection class:	II
Type of protection:	IP55
UL Type Rating:	not specified

Colours

Base unit colour:	red
Cover colour:	red

Dimensions

Width:	89 mm
Length:	43 mm
Height:	38 mm
Weight:	0.026 kg

Material characteristics

UV-resistant:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

Max. number of terminals per cross section acc. to DIN VDE 0606-1

max. amount of terminals at 1,5²:	5
max. amount of terminals at 2,5²:	3

Max. number of wires per cross section acc. to DIN VDE 0606-1

max. amount of wires at 1,5²:	15
max. amount of wires at 2,5²:	9

mechanical properties

for sealing range min:	8.2 mm
for sealing range max:	12.5 mm
Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	no
Fastening:	external fixing lugs

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	Indoors

Sales Information

EAN:	4013902610556
ETIM Class:	EC002600
Custom tariff number:	85389099
Minimum order quantity:	10

Material

Base unit material:	Polyethylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))

Accessories

68502001 - HandyGrip VG 20 - Terminal strip

68502101 - HandyGrip VG 21 - Terminal strip

68512101 - HandyGrip VG 21 w - Terminal strip

68832001 - HandyQuick SQ 32 - Screwless terminal

68852001 - HandyQuick SQ 52 - Screwless terminal

89601901 - KTB 2 - Cable tray fastening

89602901 - KTB 1-100 - Cable tray fastening

Cable gland

