




The I-ON EVO (floor-mounted) and I-ON EVO WALL (wall-mounted) charging units are JOINON's solutions for semi-public and public use, designed to withstand any impact, stress, vandalism, weather, etc. and are also prepared for full connectivity combined with the JOINON EVO platform and App. The unique hexagonal design allows the units to adapt to any urban scenario and parking configuration, with an optimal User Experience thanks to the vandal-proof plug-in modules equipped with full-color graphical displays that ensure better service fruition for the EV Driver user. They are available with standard JOINON graphics, which can be customized upon specific request.

Charging way	Mode 3	Charging sockets	Type 2
Connector type	Fixed socket (IPxxD)	Cable length (if available)	-
Electrical Characteristics INPUT	-	Power supply (input-output)	3 x 70 mm ²
Rated current	64 A	Potenza Totale	14.8 kW
Electrical Characteristics OUTPUT	-	Nominal tension	230 V
Total Maximum Current	32 A + 32 A	Power max.	7.4 kW + 7.4 kW
Thermal-magnetic protection	32 A - 2P - Curve C	Type of residual current protection	32 A - 2P - Type A
User protection	DC Leakage 6 mA	Meter	-
FUNCTIONAL CHARACTERISTICS	-	Connectivity	WiFi+Ethernet
Communication	OCPP 1.6J	Load Management	DLM/OCPP
Charging activation	RFID or APP	Human Interface	4.3" graphic display
Master/Slave	Yes	"Over-the-air" updates	Yes
Programmable Remote Contact	No	Restart	-
Local directives	-	-	-
Mechanical characteristics	-	Installation	Wall or Pole
Material	Steel sheet	External colour	Grey Chassis, Cap RAL7016
Surface treatment	Epoxy powder coating	IP degree	IP55
Mechanical resistance	IK10	Operating temperature	From -25°C to +55°C
Accessories available	-	RFID Card	GWJ8002
4G modem kits	GWJ8013	Ground fixing plate	GW46551
DLM CT KIT for load management	GWJ8037 Single-phase / GWD6809+GWD6821+C.T. (GWD96441+GWD96447) over 100 A		

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and
coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 05/08/2026

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice