

**CB-HTR 200/4,5 NC****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Our heat-stabilised cable ties made of polyamide 6.6 are suitable for continuous use at temperatures up to +125°C.

**General ordering data**

|            |                                               |
|------------|-----------------------------------------------|
| Version    | Cable ties, 4.8 x 200 mm, Polyamide 66, 220 N |
| Order No.  | <a href="#">2659460000</a>                    |
| Type       | CB-HTR 200/4,5 NC                             |
| GTIN (EAN) | 4050118682922                                 |
| Qty.       | 100 pc(s).                                    |

## CB-HTR 200/4,5 NC

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Height     | 200 mm | Height (inches) | 7.874 inch |
| Width      | 4.8 mm | Width (inches)  | 0.189 inch |
| Net weight | 0.64 g |                 |            |

## Temperatures

|                                  |              |                                  |        |
|----------------------------------|--------------|----------------------------------|--------|
| Operating temperature range      | -40...125 °C | Continuous operating temp., min. | -40 °C |
| Continuous operating temp., max. | 125 °C       |                                  |        |

## Installation materials

|                                   |        |                                   |              |
|-----------------------------------|--------|-----------------------------------|--------------|
| Bundle diameter, max.             | 50 mm  | Bundle diameter, min.             | 3 mm         |
| Cable diameter, max.              | 50 mm  | For re-opening                    | No           |
| Halogen                           | No     | Material                          | Polyamide 66 |
| Operating temperature range, max. | 125 °C | Operating temperature range, min. | -40 °C       |
| Tensile strength                  | 220 N  | Tensile strength (Pound-force)    | 49 lbf       |
| UL 94 flammability rating         | V-2    | UV-resistant                      | No           |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000046    | ETIM 7.0    | EC000046    |
| ETIM 8.0    | EC000046    | ETIM 9.0    | EC000046    |
| ETIM 10.0   | EC000046    | ECLASS 9.0  | 27-14-07-02 |
| ECLASS 9.1  | 27-14-07-02 | ECLASS 10.0 | 27-14-07-02 |
| ECLASS 11.0 | 27-14-07-02 | ECLASS 12.0 | 27-14-07-02 |
| ECLASS 13.0 | 27-14-07-02 | ECLASS 14.0 | 27-14-07-02 |
| ECLASS 15.0 | 27-14-07-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

Approvals



|                 |                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> |
| ROHS            | Conform                                                                                                                                                                     |

## Downloads

|                                             |                                              |
|---------------------------------------------|----------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">EU Declaration of Conformity</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>     |

### CB-HTR 200/4,5 NC

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

