

S-KIT OMNIMATE 4.0

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





OMNIMATE Signal and OMNIMATE Power are PCB terminal blocks, plug-in connector and panel feedthrough terminal blocks for industrial applications with a focus on signal processing and power electronics.

Power for high currents up to 232 A and voltages up to 1000 V (IEC) or 230 A at 600 V (UL). The components are optimised for application-oriented design, efficient production and reliable application.

OMNIMATE Data are RJ45 and USB circuit board sockets for safe data transmission in the Industrial Ethernet environment.

RJ45 components from Weidmüller ensure reliable transmission with high data rates up to 1 Gbit/s. With different variants for THT, THR or SMT solder processes, the female sockets are suitable for all common techniques of PCB assembly. The different design types of the RJ45 circuit board sockets allow adaptation to the individual enclosure design.

General ordering data

Sample kit	
<u>2816650000</u>	
S-KIT OMNIMATE 4.0	
4064675312857	
1 pc(s).	
Plastic box	
	2816650000 S-KIT OMNIMATE 4.0 4064675312857 1 pc(s).



S-KIT OMNIMATE 4.0

Weidmüller Interface GmbH & Co. KG

0 mm

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

0 mm

Width	0 mm	Net weight	58.96 g		
Classifications					
ETIM 6.0	EC002637	ETIM 7.0	EC002637		
ETIM 8.0	EC002637	ETIM 9.0	EC002637		
ETIM 10.0	EC002637	ECLASS 9.0	27-44-04-02		
ECLASS 9.1	27-44-04-02	ECLASS 10.0	27-44-04-02		
ECLASS 11.0	27-46-02-01	ECLASS 12.0	27-46-02-01		
ECLASS 13.0	27-46-02-01	ECLASS 14.0	27-46-02-01		
ECLASS 15.0	27-46-02-01				

Height

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption	
REACH SVHC	No SVHC above 0.1 wt%	

Approvals

Depth

ROHS	Conform	