



Main

Device short name	FDM128
Product or component type	Display module
Accessory / separate part category	Display and signalling accessory
Range compatibility	MasterPact MTZ MasterPact NW MasterPact NT Compact NSX ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200 PowerPact PowerPact H PowerPact PowerPact J PowerPact PowerPact L PowerPact PowerPact P PowerPact PowerPact R Acti 9 Acti9 Smartlink smart communication module
Product name	Enerlin'X FDM
Function of module	Remote control View network Metering Display alarm

Complementary

Control type	Remote control
Mounting mode	Flush mounting
Mounting support	Surface mount with kit
Display type	Active matrix colour TFT LCD with LED backlight
Display resolution	320 x 240 pixels QVGA
View angle horizontal x vertical	70 x 80°
[Us] rated supply voltage	24 V DC - 15...20 %
Maximum power consumption in W	6.8 W
Standards	CE CSA UL
Height	129 mm
Width	163 mm
Depth	56.5 mm
Accessory / separate part category	Spare part for ComPact NS630b...1600 Spare part for ComPact NS1600b...3200

Environment






IP degree of protection	IP54 IP65 front face:
Ambient air temperature for operation	-10...55 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.4 cm
Package 1 Width	6.8 cm
Package 1 Length	26.7 cm
Package 1 Weight	837.5 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.238 kg
Unit Type of Package 3	P12
Number of Units in Package 3	192
Package 3 Height	80 cm
Package 3 Width	120 cm
Package 3 Length	110 cm
Package 3 Weight	182.712 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------