

Product information

74 06 200 T

High Leverage Diagonal Cutter

DIN ISO 5749 IEC 60900 DIN EN 60900



⚡ 1000 V

- All-round performance: Optimum combination of cutting power, durability and ergonomics
- Cuts noticeably easier than conventional diagonal cutters of the same size thanks to the high-leverage joint
- Optimised: approximately 20% less effort compared to the previous model
- Pliers with integrated, insulated tether attachment point for a tool tether
- For very tough, continuous use
- Enables more precise work thanks to handle sleeves closer to the joint
- Redesigned handle shape for better hold
- Precision cutting edges also induction-hardened (hardness approx. 64 HRC), for all wire types including piano wire

General

Article No.	74 06 200 T
EAN	4003773081494
pliers	chrome-plated
Head	chrome-plated
Handles	insulated with multi-component grips with integrated insulated tether attachment point, VDE tested
Weight	305 g
Dimensions	200 x 58 x 27 mm
Standard	DIN ISO 5749 DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Cutting capacities medium hard wire (diameter)	Ø 4.2 mm
Cutting capacities hard wire (diameter)	Ø 3.0 mm
Cutting capacities piano wire (diameter)	Ø 2.5 mm
VDE tested	yes

technical change and errors excepted