
NH fuse enclosure

GTT 202



GTT 202

NH fuse enclosure

CUSTOMIZABLE

Productnumber: 02620201
Dimensions: 320 x 320 x 179 mm

NH fuse enclosure, 2 x NH 00 fuse switch disconnector, Shell connection 1.5 - 50 mm², PE/N terminal 2 x 50 mm², assembled on mounting plate, 3 x enclosure connectors (GGV)

with transparent cover

IP65 IK08 690V AC 440V DC

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Rated operating voltage DC:	440 V
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Protection class:	II
Type of protection:	IP65
Rated current:	160 A
UL Type Rating:	3R

Dimensions

Width:	320 mm
Length:	320 mm
Height:	179 mm
Weight:	4.372 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Impact strength:	IK08
Cover screw torque:	2.5 Nm
Stackable:	yes

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C

Ambient conditions

Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902051533
ETIM Class:	EC000249
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

07251201 - GFS 12-m - Flange set

07673001 - KPK NH00 - Prism terminal

07675001 - KSR NH 00 - Terminal screws