



Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

Complementary

Auxiliary contact composition	2 NO + 2 NC
Signalling function	Switch position (off)
Auxiliary connection terminal	Spring 0.5...1.5 mm ² (AWG 20...AWG 16)
Mounting mode	Clip-on
Mounting position	Inside front cover
[I _{th}] conventional free air thermal current	5 A
Minimum load	100 mA at 24 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Product compatibility	TA25 TR25 TA63 TR63
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.700 cm
Package 1 Width	7.000 cm
Package 1 Length	7.700 cm
Package 1 Weight	38.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	658.000 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information