


# ORION H B

Part number 3111194



## Description

Wall-mounted LED luminaire, comprising:

- Polyester powder coat finish, die-cast aluminium housing, in compact size
- Microprismatic, flat glass diffuser, silk-screened on the inside
- Aluminium reflector
- Anti-ageing custom moulded silicone sealing gasket(s)
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Stainless steel locking hardware

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

## Product data

|             |          |             |          |
|-------------|----------|-------------|----------|
| ETIM Group: | EG000027 | ETIM Class: | EC0028g2 |
|-------------|----------|-------------|----------|

## General information

|                                    |                                    |                              |        |
|------------------------------------|------------------------------------|------------------------------|--------|
| Lampholder:                        | LED                                | Light source:                | LED    |
| Lightsource lumen output [lm]:     | 1280                               | Luminaire lumen output [lm]: | 783.33 |
| Luminaire wattage [W]:             | 10 W                               | Luminous efficacy [lm/W]:    | 78     |
| CRI:                               | 80                                 | Colour temperature [K]:      | 2700   |
| Colour / Finishing:                | AN-g6 / Anthracite gray / Textured | IP degree of protection:     | IP65   |
| Impact resistance / impact energy: | IK06 1J xx3                        | Protection class:            | I      |
| Optic:                             | A/EW - Asymmetric Extra-Wide       | Net weight [kg]:             | 0.616  |
| Overall length [mm]:               | 120                                | Overall width [mm]:          | 90     |
| Overall height [mm]:               | 50                                 |                              |        |

## Mechanical features

|                    |             |                   |           |
|--------------------|-------------|-------------------|-----------|
| Shape:             | Rectangular | Housing material: | Aluminium |
| Diffuser material: | Glass       |                   |           |

## Electrical features

|                           |         |                           |         |
|---------------------------|---------|---------------------------|---------|
| Voltage type:             | AC      | Input voltage [V AC]:     | 220/240 |
| Input frequency [Hz]:     | 50/60   | Power factor / COS Φ:     | >0.9    |
| Inrush current [A/μs]:    | 3 / 135 | C10 1.5 mm <sup>2</sup> : | 133     |
| C16 2.5 mm <sup>2</sup> : | 173     | B10 1.5 mm <sup>2</sup> : | 83      |
| B16 2.5 mm <sup>2</sup> : | 133     |                           |         |

## Installation



|                                |                  |                                |               |
|--------------------------------|------------------|--------------------------------|---------------|
| Application area:              | Outdoor lighting | Mounting type:                 | Exterior wall |
| Min. ambient temperature [°C]: | -20              | Max. ambient temperature [°C]: | 40            |

## Light features

|                                 |                 |                    |               |
|---------------------------------|-----------------|--------------------|---------------|
| MacAdam:                        | 3               | Lumen maintenance: | L80B10@6680oh |
| Distribution of light emission: | Direct/Indirect |                    |               |

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

## Photometric data



To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>