CRICKET+ 10 RGBW C/M MARINE

Part number 3112275





Description

Series of reduced depth in-ground luminaires, comprising:
- Black painted anodised die-cast aluminium housing
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Closing ring in marine brass with polished finish ISO 9223 (CX)
- Mains connection through waterproof connection system (WATER-STOP)
- Technopolymer recess box to be ordered separately
- Stainless steel locking hardware
- Floor mounted luminaires are usually subject to harsh conditions. For proper use and safety, they must be correctly installed by qualified personnel and according to the manual instructions
- Do not install luminaires in sunken areas
- DMX signal generator for RGBW and Tunable White versions to be ordered separately
- The RGBW versions to be powered with 48V DC SELV drivers, available as accessories. Colour management through DMX interface

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC000758

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	130	**Luminaire lumen output [lm]:**	100
Luminaire wattage [W]:	3.5 W	**Luminous efficacy [lm/W]:**	29
CRI:	80	**Colour temperature [K]:**	rgbw 4000
Colour / Finishing:	BR-10 / Natural brass / Glossy	**IP degree of protection:**	IP67
Impact resistance / impact energy:	IK08 9J xx5	**Protection class:**	III
Optic:	C/M - Circular Medium	**Beam angle:**	30°
Net weight [kg]:	0.698	**Overall diameter [mm]:**	105
Overall height [mm]:	82		

Mechanical features

Shape:	Round ≤ 150 mm	**Housing material:**	Aluminium
Diffuser material:	Glass	**Glow wire test [°C]:**	650 °C
Dinamic load [kg]:	6000	**Speed [km/h]:**	30
Static load [kg]:	2000	**Shear load [kN]:**	5
Resistance to torque [Nm]:	50		

Electrical features

Voltage type:	DC	**Input voltage [V DC]:**	44/52

Installation

Application area:	Outdoor lighting	**Mounting type:**	Inground
Min. ambient temperature [°C]:	-20	**Max. ambient temperature [°C]:**	30
Glass temperature [°C]:	36	**Ingrounds classification:**	A1 A2 A3 A4 A5
Min. distance from lighted object [m]:	0.50		

Light features

Lumen maintenance:	L80B10@50000h	**Distribution of light emission:**	Direct

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Control gear

CRICKET+ 10 MARINE RGBW / CRICKET+ 10 MARINE TW

310950

Driver - CV 100 W - 48 V kit

310951

Driver - CV 500 W - 48 V kit

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

3117844

Controller DMX touch white

WH-87 / White

3117845

Controller DMX touch black

BK-81 / Black

3115612

USB key EcoEcco

Mandatory accessories

CRICKET+ 10 MARINE RGBW / CRICKET+ 10 MARINE TW



3113571

Recessed box CRICKET+ 10 RGBW/TW

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com