

XDAL11331

Pre cabled 2 axis joystick controller, Harmony
XDA, analog omnidirectional, 12...24 V DC

Main

Range of product	Harmony XDA
Product or component type	Pre-cabled 2 axis joystick controller
Device short name	XDA
Type of output signal	Analogue
Bezel material	Chromium plated metal
Additional information	With blank legend plate
Sale per indivisible quantity	1
Mechanical interlocking	Without zero position mechanical interlock
[Us] rated supply voltage	12...24 V DC
Current consumption	<= 25 mA at 26 ° 4 mA at zero position
Protection type	Short-circuit protection on output Reverse polarity protection

Complementary

Mounting diameter	22 mm
Net weight	0.15 kg
Shape of signaling unit head	Round
Operator profile	Operating shaft
Operator direction information	Omnidirectional
Maximum displacement angle	26 ° (+/- 1 °)
Mechanical durability	3000000 cycles
Operating force	10 N at 26 ° 3.5 N at 3 °
Mounting support	Panel - thickness: 1...4.5 mm
Cable length	0.5 m
Wire section	0.2 mm ²

Environment

Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Electrical shock protection class	Class II conforming to IEC 60536 Class II conforming to NF C 20-030
IP degree of protection	IP65 conforming to IEC 60536 IP65 conforming to NF C 20-010
Standards	NF C 63-140 IEC 60337-1 VDE 0660-200
Vibration resistance	13 gn (f= 10...500 Hz) conforming to IEC 60068-2-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	9.0 cm
Package 1 Length	15.5 cm
Package 1 Weight	182.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.652 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations