Busbar terminal

SKL 330



SKL 330

Busbar terminal

Productnumber: 07533001
Dimensions: 51 x 41 x 85,5 mm

Busbar terminal, for large connection cross-sections, for copper rails 20 x 5 mm to 30 x 10 mm

for CU conductors 1x (120-300)rm/rf/sm, aluminium conductor see technical appendix

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Max. conductor cross section:	300 mm²
Rated current:	420 A
Number of poles:	1
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	1
Connection 1: Suitable for Cu conductors:	1
Connection 1: Suitable for Al conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	95 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	300 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	95 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	300 mm²

Dimensions

Width:	51 mm
Length:	41 mm
Height:	85.5 mm
Weight:	0.407 kg

mechanical properties

Connection 1: Tightening moment:	36 Nm

Sales Information

EAN:	4013902051984
ETIM Class:	EC000001
Custom tariff number:	85369010
Minimum order quantity:	1