

**WQB B/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image****General ordering data**

|            |                                                                                                                                      |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 15.28 mm |
| Order No.  | <a href="#">1579020000</a>                                                                                                           |
| Type       | WQB B/3                                                                                                                              |
| GTIN (EAN) | 4008190062392                                                                                                                        |
| Qty.       | 50 pc(s).                                                                                                                            |

## WQB B/3

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 2.5 mm   | Depth (inches)  | 0.098 inch |
| Height     | 23.5 mm  | Height (inches) | 0.925 inch |
| Width      | 15.28 mm | Width (inches)  | 0.602 inch |
| Net weight | 0.95 g   |                 |            |

## Temperatures

|                                  |                |                     |               |
|----------------------------------|----------------|---------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
| Continuous operating temp., max. | 70 °C          |                     |               |

## Material data

|          |               |        |       |
|----------|---------------|--------|-------|
| Material | tinned copper | Colour | black |
|----------|---------------|--------|-------|

## System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

## Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No              | Installation advice | Direct mounting |
| Type of fixing           | when screwed in |                     |                 |

## Cross-connector

|                                     |                 |                           |      |
|-------------------------------------|-----------------|---------------------------|------|
| Number of cross-connected terminals | 3               | Rated current, multi-pole | 24 A |
| Type                                | Cross-connector |                           |      |

## Dimensions

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|

## General

|                     |                 |                 |   |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 3 |
|---------------------|-----------------|-----------------|---|

## Rating data

|               |       |               |      |
|---------------|-------|---------------|------|
| Rated voltage | 800 V | Rated current | 24 A |
|---------------|-------|---------------|------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

Creation date May 11, 2025 6:36:57 PM CEST

Catalogue status 26.04.2025 / We reserve the right to make technical changes.

## WQB B/3

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |