

**MODUFLEX C-MW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The coupling frame can be mounted on a flat surface using the installation bracket for the ModuFlex-C coupling frame system. The installation bracket is designed so that it can be installed from either the front or back.

**General ordering data**

|            |                                                      |
|------------|------------------------------------------------------|
| Version    | Heavy-duty connectors, MODUFLEX C, Modulflex C frame |
| Order No.  | <a href="#">1746070000</a>                           |
| Type       | MODUFLEX C-MW                                        |
| GTIN (EAN) | 4008190986483                                        |
| Qty.       | 10 pc(s).                                            |

**MODUFLEX C-MW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Dimensions and weights**

|            |       |
|------------|-------|
| Net weight | 7.9 g |
|------------|-------|

**ConCept Pneumatic module**

|        |      |
|--------|------|
| Colour | grey |
|--------|------|

**General data**

|                               |       |                    |                   |
|-------------------------------|-------|--------------------|-------------------|
| Colour                        | grey  | Free from halogens | false             |
| Low smoke acc. DIN EN 45545-2 | Yes   | Series             | Modulflex C frame |
| Type                          | other |                    |                   |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002943    | ETIM 7.0    | EC002943    |
| ETIM 8.0    | EC002943    | ETIM 9.0    | EC002943    |
| ETIM 10.0   | EC002943    | ECLASS 9.0  | 27-44-02-92 |
| ECLASS 9.1  | 23-15-90-90 | ECLASS 10.0 | 27-44-02-92 |
| ECLASS 11.0 | 27-44-02-92 | ECLASS 12.0 | 27-44-02-92 |
| ECLASS 13.0 | 27-44-02-92 | ECLASS 14.0 | 27-44-02-92 |
| ECLASS 15.0 | 27-44-02-92 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
| Brochures  | <a href="#">FL FIELDWIRING EN</a>        |

**MODUFLEX C-MW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Mounting feet**

Mounting feet are used to mount components that cannot be snapped directly on a DIN rail.

**General ordering data**

|            |                            |                          |
|------------|----------------------------|--------------------------|
| Type       | MOFU 35                    | Version                  |
| Order No.  | <a href="#">0495660000</a> | Mounting foot (terminal) |
| GTIN (EAN) | 4008190048518              |                          |
| Qty.       | 20 pc(s).                  |                          |