



Hoofd

Range	Canalis
Type aanbod	Klassiek Controlesysteem
Product or component type	Connector
Device application	Verlichting Stopcontact distributie
Bereik compatibiliteit	Canalis KBA railkokersysteem Canalis KBB railkokersysteem
Ie toegekende bedrijfstrom	10 A bij 35 °C
[Ue] rated operational voltage	230...240 V
Network frequency	50/60 Hz
Protocol communicatiepoort	DALI
Polariteit aftakeenheid	L1 + N + PE L2 + N + PE L3 + N + PE L1 + L2 + PE L1 + L3 + PE L2 + L3 + PE
Aftakeenheid connectortype	Met faseselectie

Complementair

Colour	Crème (RAL 9001)
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	690 V
Type bescherming	Zonder beveiliging
Width	1 m
Depth	62 mm
Height	60 mm
Net weight	65 g
Quantity per set	Set van 10
Standards	EN/IEC 61439-1 EN/IEC 61439-6

Omgeving

IP beschermingsgraad	IP55 conforming to EN/IEC 60529
----------------------	---------------------------------

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6,000 cm
Package 1 Width	6,000 cm
Package 1 Length	11,500 cm
Package 1 Weight	66,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	12,500 cm

Package 2 Width	13,600 cm
Package 2 Length	32,000 cm
Package 2 Weight	802,000 g
Unit Type of Package 3	P06
Number of Units in Package 3	500
Package 3 Height	75,000 cm
Package 3 Width	60,000 cm
Package 3 Length	80,000 cm
Package 3 Weight	40,075 kg

Duurzaamheid van het aanbod

REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet  EU-verklaring RoHS
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.
PVC-vrij	Ja
Aanwezigheid van halogeen	Product met halogeenvrije kunststof onderdelen

contractuele waarborg

Garantie	18 months
----------	-----------