Enclosure with sliding seal

SVi LS-g



SVi LS-g

Enclosure with sliding seal

Productnumber: 59112201
Dimensions: 150 x 300 x 137 mm

Empty enclosure, with sliding seal and cable clamp

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Protection class:	II
Type of protection:	IP54
UL Type Rating:	not specified

Dimensions

Width:	150 mm
Length:	300 mm
Height:	137 mm
Inner height:	119 mm
Weight:	1.2 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Surface mounted
Impact strength:	IK07

Ambient conditions

Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902568376
ETIM Class:	EC000058

Sales Information

Custom tariff number:	85389099
Minimum order quantity:	1

Material

Base unit material:	Plastic

Cable gland

