


| | | | |
|---|---|---|---|
| **EAN:** | 4013288155474 | **Size:** | 89x7x6 mm |
| **Part number:** | 05059660001 | **Weight:** | 25 g |
| **Article number:** | 840/4 Z Hex-Plus | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82079030 |

- For hexagonal socket head screws
- Hex-Plus allows socket head screws to live longer
- Tough for hard materials
- 1/4" hexagon drive (Wera connecting series 4)

Tough Wera bits for hexagonal socket screws, for universal use. Hex-Plus offers larger contact surfaces in the screw head. The notch effect is reduced to a minimum and the destruction of the screw is nearly eliminated. 1/4" hexagonal, suitable for holders as per DIN ISO 1173-F 6.3.

**Web link**
https://www.wera.de/en/05059660001



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

## Hex-Plus



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

## Tough bits




Tough Wera bits prevent the tip from breaking prematurely. Z-bits usually are the bit for universal screwdriving applications.

## Further versions in this product family:

| | mm | inch | mm | inch | mm |
|---|---|---|---|---|---|
| 05160885001 | 0.9 | - | 50 | 2" | 2.6 |
| 05059602001 | 1.5 | - | 50 | 2" | 2.0 |
| 05059603001 | 2.0 | - | 50 | 2" | 4.0 |
| 05059628001 | 2.0 | - | 89 | 3 1/2" | 4.0 |
| 05059604001 | 2.5 | - | 50 | 2" | 4.0 |
| 05059629001 | 2.5 | - | 89 | 3 1/2" | 4.0 |
| 05059605001 | 3.0 | - | 50 | 2" | 4.0 |
| 05059630001 | 3.0 | - | 89 | 3 1/2" | 4.0 |
| 05380033001 | 3.0 | - | 152 | 6" | 4.0 |
| 05059610001 | 4.0 | - | 50 | 2" | 5.0 |
| 05059631001 | 4.0 | - | 89 | 3 1/2" | 5.0 |
| 05059634001 | 4.0 | - | 152 | 6" | 5.0 |
| 05059615001 | 5.0 | - | 50 | 2" | 6.0 |
| 05059632001 | 5.0 | - | 89 | 3 1/2" | 6.0 |
| 05059635001 | 5.0 | - | 152 | 6" | 6.0 |
| 05059620001[1)] | 6.0 | - | 50 | 2" | 5.0 |

**Web link**
https://www.wera.de/en/05059660001

Wera - 840/4 Z Hex-Plus
05059660001 - 4013288155474

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

| | | | | | |
|---|---|---|---|---|---|
| 05059633001[1] | 6.0 | - | 89 | 3 1/2" | - |
| 05059636001[1] | 6.0 | - | 152 | 6" | - |
| 05059625001[1] | 8.0 | - | 50 | 2" | - |
| 05059637001[1] | 8.0 | - | 89 | 3 1/2" | - |
| 05350430001 | - | 0.05" | 50 | 2" | 2.5 |
| 05135090001 | - | 1/16" | 50 | 2" | 2.5 |
| 05135091001 | - | 5/64" | 50 | 2" | 3.0 |
| **05059660001** | **-** | **5/64"** | **89** | **3 1/2"** | **3.0** |
| 05135092001 | - | 3/32" | 50 | 2" | 3.0 |
| 05059661001 | - | 3/32" | 89 | 3 1/2" | 3.5 |
| 05135093001 | - | 7/64" | 50 | 2" | 3.5 |
| 05059662001 | - | 7/64" | 89 | 3 1/2" | 4.0 |
| 05135094001 | - | 1/8" | 50 | 2" | 4.0 |
| 05059663001 | - | 1/8" | 89 | 3 1/2" | 4.0 |
| 05380045001 | - | 1/8" | 152 | 6" | 4.0 |
| 05135095001 | - | 9/64" | 50 | 2" | 4.5 |
| 05059664001 | - | 9/64" | 89 | 3 1/2" | 4.5 |
| 05380046001 | - | 9/64" | 152 | 6" | 4.5 |
| 05135096001 | - | 5/32" | 50 | 2" | 5.0 |
| 05059665001 | - | 5/32" | 89 | 3 1/2" | 5.0 |
| 05380047001 | - | 5/32" | 152 | 6" | 5.0 |
| 05135097001 | - | 3/16" | 50 | 2" | 6.0 |
| 05059666001 | - | 3/16" | 89 | 3 1/2" | 6.0 |
| 05380048001 | - | 3/16" | 152 | 6" | 6.0 |
| 05135098001 | - | 7/32" | 50 | 2" | - |
| 05059667001 | - | 7/32" | 89 | 3 1/2" | - |
| 05380049001 | - | 7/32" | 152 | 6" | - |
| 05135099001 | - | 1/4" | 50 | 2" | - |
| 05059668001 | - | 1/4" | 89 | 3 1/2" | - |
| 05380050001 | - | 1/4" | 152 | 6" | - |
| 05346288001 | - | 5/16" | 50 | 2" | - |

1) Hexagonal blade

**Web link**
https://www.wera.de/en/05059660001

Wera - 840/4 Z Hex-Plus
05059660001 - 4013288155474

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de