

QL 3 SAK16


Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



In contrast to the terminal blocks with integrated disconnect lever, our disconnect plugs can be completely detached or removed from the terminal block and the respective application and offer a flexible alternative solution to our standard disconnectors.

General ordering data

| | |
|------------|---|
| Version | Cross-connector (terminal), when screwed in, grey, 76 A, Number of poles: 3, Pitch in mm (P): 6.00, Insulated: No, Width: 29.8 mm |
| Order No. | 0470800000 |
| Type | QL 3 SAK16 |
| GTIN (EAN) | 4008190011574 |
| Qty. | 50 items |

Technical data

Approvals

ROHS Conform

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 2 mm | Depth (inches) | 0.0787 inch |
| Height | 6 mm | Height (inches) | 0.2362 inch |
| Width | 29.8 mm | Width (inches) | 1.1732 inch |
| Net weight | 2.48 g | | |

Temperatures

Storage temperature -25 °C...55 °C Ambient temperature -5 °C...40 °C

Environmental Product Compliance

RoHS Compliance Status Compliant without exemption
 REACH SVHC No SVHC above 0.1 wt%

Material data

Basic material Cu Zn Colour grey

System specifications

Version for cross-connection link

Additional technical data

Type of fixing when screwed in Installation advice Direct mounting
 Explosion-tested version No

Dimensions

Pitch in mm (P) 6.00 mm

General

Number of poles 3 Installation advice Direct mounting

Rating data

Nominal current 76 A

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |
| ETIM 10.0 | EC000489 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 | | |

QL 3 SAK16

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Accessories

Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

| | | | |
|------------|----------------------------|---|--|
| Type | VH 12/4.9/3.3 | Version | |
| Order No. | 0249000000 | Connecting sleeve (terminal), when screwed in, Width: 4.9 mm, | |
| GTIN (EAN) | 4008190129507 | Height: 4.9 mm, Depth: 12 mm, Number of poles: 1, Copper | |
| Qty. | 100 ST | | |

Disconnect plugs




In contrast to the terminal blocks with integrated disconnect lever, our disconnect plugs can be completely detached or removed from the terminal block and the respective application and offer a flexible alternative solution to our standard disconnectors.

General ordering data

| | | | |
|------------|----------------------------|--------------------------------------|--|
| Type | KISC M3X20.5/10 EK4 | Version | |
| Order No. | 0303000000 | Clamping yoke, Mounting screw, Steel | |
| GTIN (EAN) | 4008190163686 | | |
| Qty. | 100 ST | | |

Cross-connections



The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

| | | | |
|------------|----------------------------|---------------------|--|
| Type | SS M3 D 128-A 3 | Version | |
| Order No. | 0164400000 | Lock washer, Copper | |
| GTIN (EAN) | 4008190035914 | | |
| Qty. | 50 ST | | |