

# LANTERNA NK 27

Part number 3102164



## Description

Series of wall mounted luminaires in two sizes for indoor and outdoor, comprising:

- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Pressed glass diffuser, internally coated, secured with the ring
- Transparent, pressed glass diffuser (E27 versions)
- Aluminium reflector and gear tray
- Technopolymer silicone sealing gasket
- Burnished stainless steel fixing screws
- Built-in driver
- Design by ROBERTO FIORATO

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

## Product data

|             |          |             |          |
|-------------|----------|-------------|----------|
| ETIM Group: | EG000027 | ETIM Class: | EC001745 |
|-------------|----------|-------------|----------|

## General information

|                          |         |                                    |                         |
|--------------------------|---------|------------------------------------|-------------------------|
| Lampholder:              | E27     | Light source:                      |                         |
| Luminaire wattage [W]:   | 1x100 W | Colour / Finishing:                | RB-10 / Rust / Textured |
| IP degree of protection: | IP65    | Impact resistance / impact energy: | IK08 5J xx5             |
| Protection class:        | I       | Optic:                             | -                       |
| Net weight [kg]:         | 2.785   | Overall length [mm]:               | 200                     |
| Overall width [mm]:      | 146     | Overall height [mm]:               | 278                     |

## Mechanical features

|                    |             |                   |           |
|--------------------|-------------|-------------------|-----------|
| Shape:             | Rectangular | Housing material: | Aluminium |
| Diffuser material: | Glass       |                   |           |

## Installation

|                                |                  |                                |          |
|--------------------------------|------------------|--------------------------------|----------|
| Application area:              | Outdoor lighting | Mounting type:                 | Bulkhead |
| Min. ambient temperature [°C]: | -30              | Max. ambient temperature [°C]: | 25       |

## Light features

|                                 |        |
|---------------------------------|--------|
| Distribution of light emission: | Direct |
|---------------------------------|--------|

---

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

For information:  
**PERFORMANCE IN LIGHTING S.p.A. Headquarters - Italy**  
Viale del Lavoro 9/11  
37030 Colognola ai Colli Verona - Italy  
Tel. +39 045 61 59 211

**info.it@pil.lighting**  
[www.performanceinlighting.com](http://www.performanceinlighting.com)