Cone funnel

KOT 40



KOT 40

Cone funnel

Productnumber: 97063701
Dimensions: 71 x 71 x 114,9 mm

Cone funnel, for wall-to-wall connections or wall-ceiling transfers in large panel constructions and for connections from risers (e.g. telephone TV) also suitable for magnet fixing and opposing formwork, rated insulation voltage: 400V AC, Halogen free

magnet and nail installation, sealing range M40, support spar compatible

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Suitable for:	Concrete construction

Dimensions

Width:	71 mm
Length:	71 mm
Height:	114.9 mm
Weight:	0.047 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	magnet and nail installation

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902891993
ETIM Class:	EC002328
Custom tariff number:	39269097
Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Accessories

97924001 - NAS-AL - IBT Accessories

97924201 - NA-AL - IBT Accessories

97924301 - NA-AL/gl - IBT Accessories

97953601 - STH-ELP - Cartridge insert

97957001 - STH 70 - Support spar

97959001 - STH 90 - Support spar

97960001 - STH 100 - Support spar

97961001 - STH 110 - Support spar

97963001 - STH 130 - Support spar

97964001 - STH 140 - Support spar

97965001 - STH 150 - Support spar

97967001 - STH 170 - Support spar

97969001 - STH 190 - Support spar

97973001 - STH 230 - Support spar

97974001 - STH 240 - Support spar

97979001 - STH 290 - Support spar

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299