Universal outlet cleats

DAL 1



DAL 1

Universal outlet cleats

Productnumber: 97070501
Dimensions: 49 x 171 x 35 mm

Universal outlet cleats, usable as a ceiling outlet with a large tolerance compensation, protection class IP00, rated insulation voltage: 400V AC, Halogen free

DAL 1 and DAL 2 can be combined next to each other and one behind the other without tools, adhesive fixing or nail installation, sealing range M20 - M25

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Type of protection:	IP00
Suitable for:	Concrete construction
UL Type Rating:	not specified

Dimensions

Width:	49 mm
Length:	171 mm
Height:	35 mm
Weight:	0.0255 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	adhesive fixing or nail installation

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902911509
ETIM Class:	EC002601
Custom tariff number:	39269097

Sales Information

Minimum order quantity:	1

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Accessories

23162001 - VST M20/or - Sealing plugs

23162501 - VST M25/or - Sealing plugs

97924001 - NAS-AL - IBT Accessories

97924201 - NA-AL - IBT Accessories

97924301 - NA-AL/gl - IBT Accessories