

Junction box

Abox Pro SLK-4²/sw



Abox Pro SLK-4²/sw

Junction box

Productnumber: 40407001

Dimensions: 102 x 102 x 70 mm

Junction box, protection class IP66/IP67/IP69, nominal cross-section 4 mm², Ui=450 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), DLG (Ammonia resistance), DNV (Class: Ships and Offshore Installations), knockouts, M16/M20/M25, (1 rear, 7 side), internal fixing points, with screwless terminals and clamp holder, for installation in industrial environments and unprotected outdoor areas

black, In=32 A, with 5 floor-fixed, screwless 3-wire terminals, Wago 221-413 - 4 mm², clampable cross-sections per pole: 3 x 0.2 to 4 mm² rigid Cu and 3 x 0.14 to 4 mm² flexible Cu

Accessories supplied:

4 double membrane seals IP66 M25 sealing range 9 - 17 mm, cover retainer



Technical Data

electrical characteristics

Rated insulation voltage AC:	450 V
Rated insulation voltage DC:	450 V
Min. conductor cross section:	0,2 mm ²
Max. conductor cross section:	4 mm ²
Protection class:	II
Type of protection:	IP66/IP67/IP69
Rated current:	32 A
Terminal type:	screwless
Number of poles:	5

Colours

Base unit colour:	black
Cover colour:	black

Dimensions

Width:	102 mm
Length:	102 mm
Height:	70 mm
Inner length:	88 mm
Inner width:	88 mm
Inner height:	50 mm
Weight:	0.2332 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V0
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Impact strength:	IK09
Sealable:	yes
Cover screw torque:	1.5 Nm
Type of fastening:	Wall/ceiling mounting
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	unprotected outdoor areas

Sales Information

EAN:	4013902703593
ETIM Class:	EC002600
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel 1.4567 (V2A)

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
Test mark:	DLG (Ammonia resistance)
Test mark:	DNV (Class: Ships and Offshore Installations)

Accessories

[22701601 - KVR M16-MGM/sw - Cable gland](#)

[22702101 - KVR M20-GDB/MGM/sw - Cable gland](#)

[22702001 - KVR M20-MGM/sw - Cable gland](#)

[22702501 - KVR M25-MGM/sw - Cable gland](#)

[26001601 - DMS M16/sw - Double-membrane seals](#)

[26002001 - DMS M20/sw - Double-membrane seals](#)

[26002501 - DMS M25/sw - Double-membrane seals](#)

[89602901 - KTB 1-100 - Cable tray fastening](#)

Cable gland

