Charging cable

# LL 7m T2



## LL 7m T2

**Charging cable**

Productnumber: 59181001
Dimensions: 12,8 x 7000 x 12,8 mm

Charging cable – AC charging cable with Type 2 charging plug in accordance with IEC 62196 and open cable ends, with cap, cable construction 5 x 2.5 mm² + 1 x 0.5 mm², IP54 (with cap), charging power up to max. 11 kW (3-phase), charging current up to max. 16 A, for installation on a Spelsberg Wallbox

**7m length with Type 2 plug**

IP54 400V AC


Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

# Technical Data

## electrical characteristics

| | |
|---|---|
| max. charging power: | 11 kW |
| max. charging current: | 16 A |
| System side connection: | 3-phase |
| Rated operating voltage AC: | 400 V |
| Charging mode (IEC 61851): | 3 C |
| Long charging cable: | 7 m |
| Connector plug: | Type 2 |
| Type of protection: | IP54 |
| Rated current: | 16 A |
| Number of power contacts: | 5 |
| Number of signal contacts: | 2 |
| Signal contacts rated current: | 2 A |
| Signal contacts rated voltage: | 30 V |
| Cable type: | straight |

## Colours

| | |
|---|---|
| Accessory colour: | deep black |

## Dimensions

| | |
|---|---|
| Width: | 12.8 mm |
| Length: | 7000 mm |
| Height: | 12.8 mm |
| Diameter: | 12.8 mm |
| Weight: | 2.28 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |

## Sales Information

| | |
|---|---|
| EAN: | 4013902673650 |
| ETIM Class: | EC002897 |
| Custom tariff number: | 85444290 |
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Accessory material: | insulating material |