E-Bike charging station

TG BCS 3 BE/FR LED



TG BCS 3 BE/FR LED

E-Bike charging station

Productnumber: 20013401
Dimensions: 202 x 152 x 110 mm

E-Bike charging station, protection class IP44, black, incl. cover screw with special head, cable entries, 1 x M25 rear housing side, 1 x M25 lower housing side, 1 x ventilation seal M20, pre-wired to terminal Wago 221 (L1/L2/L3/N/PE)
Cable insertions:
Bottom: DMS 1 x M25
Rear: DMS 1 x M25

with LED lighting
equipped with:
• 3 x Protective contact socket, French/Belgian standard (on front), 230V

Technical Data

Built-in devices

Protective contact socket, French/Belgian standard (on front), 230V :	3

electrical characteristics

Rated insulation voltage AC:	400 V
Protection class:	II
Type of protection:	IP44
Number of rows:	IP44

Colours

Base unit colour:	black
Cover colour:	black

Dimensions

Width:	202 mm
Length:	152 mm
Height:	110 mm
Inner length:	195 mm
Inner width:	145 mm
Inner height:	76 mm
Weight:	0.8089 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	750 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Wall mounting

mechanical properties

Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902611768
ETIM Class:	EC002883
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Stainless steel 1.4567 (V2A)

Accessories

20003101 - BCS WP1 - Weather protection cover

20003201 - BCS WP2 - Earth spike

20003301 - Bit TX20-89 - Special Bit

Cable gland

