

**KSW 4 16/3,5 1-16****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

KSW marking strips are used to identify multi-pole PCB plug-in connectors. Users can print them individually without being confined to a certain pitch.

- Smudge-proof labelling
- Strips 2.5 mm and 4 mm wide
- Simply stick on - finished
- Optimum adhesion
- PVC-free

**General ordering data**

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| Version    | KSW, Terminal marker, 4 x 56 mm, Pitch in mm (P): 3.50 Weidmueller, white |
| Order No.  | <a href="#">1630150001</a>                                                |
| Type       | KSW 4 16/3,5 1-16                                                         |
| GTIN (EAN) | 4008190214555                                                             |
| Qty.       | 10 pc(s).                                                                 |

## KSW 4 16/3,5 1-16

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |       |                 |            |
|------------|-------|-----------------|------------|
| Height     | 4 mm  | Height (inches) | 0.157 inch |
| Width      | 56 mm | Width (inches)  | 2.205 inch |
| Net weight | 1 g   |                 |            |

## Temperatures

|                             |        |
|-----------------------------|--------|
| Operating temperature range | 150 °C |
|-----------------------------|--------|

## General data

|                                   |                     |                                              |               |
|-----------------------------------|---------------------|----------------------------------------------|---------------|
| Adhesive                          | Acrylate            | Application/manufacturer                     | Weidmueller   |
| Colour                            | white               | Colour of printing                           | black         |
| Material                          | Polyester, PVC-free | Material colour according to resistance code | 9             |
| Number per sheet                  | 20                  | Operating temperature range                  | 150 °C        |
| Operating temperature range, max. | 150 °C              | Orientation of print                         | horizontal    |
| Printed characters                | Numbers             | Printing                                     | 1 - 16        |
| Printing method                   | Thermal transfer    | Version                                      | Self-adhesive |
| Width                             | 56 mm               |                                              |               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000761    | ETIM 7.0    | EC000761    |
| ETIM 8.0    | EC000761    | ETIM 9.0    | EC000761    |
| ETIM 10.0   | EC000761    | ECLASS 9.0  | 27-14-11-37 |
| ECLASS 9.1  | 27-14-11-37 | ECLASS 10.0 | 27-14-11-37 |
| ECLASS 11.0 | 27-28-11-01 | ECLASS 12.0 | 27-28-11-01 |
| ECLASS 13.0 | 27-28-11-01 | ECLASS 14.0 | 27-28-11-01 |
| ECLASS 15.0 | 27-28-11-01 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
| Brochures  |                                          |