


Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Power feed-in

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

Version	PE terminal, PUSH IN, 35 mm², 1000 V, Green/yellow
Order No.	<u>2735950000</u>
Туре	A2C 35 PE DL
GTIN (EAN)	4064675002673
Qty.	10 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

-			
Dim	ensions	and	weights

Depth	71.5 mm	Depth (inches)	2.815 inch
Height	101 mm	Height (inches)	3.976 inch
Width	16 mm	Width (inches)	0.63 inch
Net weight	115.2 g	-	

Temperatures

Storage temperature	-25 °C55 °C	Continuous operating temp., min.	-60 °C	
Continuous operating temp max	130 °C			

Material data

Material	Wemid	Colour	Green/yellow
Colour of operational elements	orange	UL 94 flammability rating	V-0

Rating data IECEx/ATEX

Certificate No. (ATEX)	TUEV16ATEX7909U	Certificate No. (IECEX)	IECEXTUR16.0036U
Wire cross section max. (ATEX)	35 mm ²	Wire cross section max. (IECEX)	35 mm²

System specifications

End cover plate required	No	Number of potentials	1
Number of levels	1	Number of clamping points per level	2
Rail	TS 35	N-function	No
PE function	Yes	PEN function	No

Additional technical data

Explosion-tested version	Yes	Snap-on	Yes	
Type of fixing	Snap-on	Type of mounting	Snap-on	

Conductors for clamping (additional connection)

Connection type, additional connection PUSH IN



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

Blade size	1.0 x 5.5 mm	Clamping range, max.	35 mm ²
Clamping range, min.		Connection cross-section, stranded,	
	2.5 mm ²	max.	35 mm ²
Connection cross-section, stranded, mir	n. 10 mm²	Connection direction	on side
Number of connections	2	Stripping length	25 mm
Twin wire-end ferrules, max.	10 mm ²	Twin wire-end ferrules, min.	2.5 mm ²
Type of connection	PUSH IN	Wire connection cross section AWG, max.	AWG 2
Wire connection cross section AWG, min.	AWG 12	Wire connection cross section, finely stranded, max.	35 mm²
Wire connection cross section, finely stranded, min.	10 mm²	Wire connection cross-section, fine- ly stranded with wire-end ferrules DIN 46228/1, max.	35 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	2.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	35 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	2.5 mm ²	Wire connection cross-section, solid core, max.	16 mm²
Wire connection cross-section, solid core, min.	2.5 mm ²		

Rail	TS 35	Standards	IEC 60947-7-2
Wire connection cross section AWG,	_	Wire connection cross section AWG,	
max.	AWG 2	min.	AWG 12

Rating data

Rated cross-section	35 mm ²	Rated voltage	1,000 V
Rated voltage to adjoining terminal	1,000 V	Rated DC voltage	1,500 V
Standards		Volume resistance according to IEC	
	IEC 60947-7-2	60947-7-x	$0.26~\text{m}\Omega$
Power loss in accordance with IEC		Pollution severity	
60947-7-x	4 W		3
Surge voltage category	III		

Classifications

ETIM 6.0	EC000901	ETIM 7.0	EC000901
ETIM 8.0	EC000901	ETIM 9.0	EC000901
ETIM 10.0	EC000901	ECLASS 9.0	27-14-11-41
ECLASS 9.1	27-14-11-41	ECLASS 10.0	27-14-11-41
ECLASS 11.0	27-14-11-41	ECLASS 12.0	27-14-11-41
ECLASS 13.0	27-25-01-03	ECLASS 14.0	27-25-01-03
ECLASS 15.0	27-25-01-03		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

Approvals







Approvals MAMID https://mdcop.weidmueller.com/mediadelivery/rendition/900_319217/-T1z1mm-S800/ https:// mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://

mdcop.weidmueller.com/mediadelivery/rendition/900_319240/-T1z1mm-S800/ https:// $mdcop.weidmueller.com/mediadelivery/rendition/900_319244/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_319244/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_31924/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_31924/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_31924/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_31924/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_31924/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900$ $mdcop.weidmueller.com/mediadelivery/rendition/900_319213/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900_319213/-T1z1mm-S800/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/rendition/900/\ https://discom/mediadelivery/renditio$ mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/

ROHS Conform

Downloads

Approval/Certificate/Document of Con- Attestation of Conformity

formity CE Declaration of Conformity

UKCA declaration of conformity Confirmation of Standards EN 45545-2_2020-10

Engineering Data CAD data - STEP




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings







Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

DEK 5/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Type DEK 5/5 MM WS
Order No. 2007110000
GTIN (EAN) 4050118391862
Oty. 800 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Weidmueller, white

Digital multimeters



Multimeters are capable of measuring a number of variables. Each instrument can measure voltage and resistance, as well as performing continuity and diode testing as standard.

In addition, the individual multimeters also feature extra measuring options such as current, frequency, capacitance and temperature. Digital multimeters have the advantage of a clear display which can be read easily and directly. With these instruments, mistakes arising from faulty conversion of the measuring ranges or misreading the display are a thing of the past.

General ordering data

Type ZUB MULTIMETER
Order No. 9205270000
GTIN (EAN) 4032248723522
Qty. 1 pc(s).

Version Multimeter

Creation date May 11, 2025 10:10:09 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon[®] Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Туре	BZT 1 ZA WS 10/5	Version
Order No.	<u>1805520000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 pc(s).	
Туре	BZT 1 WS 10/5	Version
Order No.	<u>1805490000</u>	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 pc(s).	

2.5 mm²

2.5

 mm^2

End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

GCIICIUI	denotal ordering data	
Туре	AEP 3T 2.5	Version
Order No.	<u>2428560000</u>	A-series, End plate
GTIN (EAN)	4050118438246	
Qty.	20 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General	ordering data	
Туре	WS 8/5 PLUS MC NE WS	Version
Order No.	<u>1951870000</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248631605	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 8/5 MC NE RT	Version
Order No.	<u>1773521686</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141531	Allen-Bradley, red
Qty.	720 pc(s).	
Туре	WS 8/5 MC NE WS	Version
Order No.	<u>1640740000</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190279103	Allen-Bradley, white
Qty.	720 pc(s).	
Туре	WS 8/5 MC NE OR	Version
Order No.	<u>1773521690</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248143092	Allen-Bradley, orange
Qty.	720 pc(s).	
Туре	WS 8/5 MC NE GE	Version
Order No.	<u>1773521687</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141548	Allen-Bradley, yellow
Qty.	720 pc(s).	
Туре	WS 8/5 MC NE BL	Version
Order No.	<u>1773521693</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141715	Allen-Bradley, blue
O (2,)		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Slotted screwdriver



VDE insulated screwdriver sets, for working on live parts up to 1000 V AC and 1500 V DC, DIN EN 60900. IEC 900. Each piece is "GS" safety tested. Blade made from fully hardened, high-alloy chromium-vanadium-molybdenum steel, gun-metal finish.

General ordering data

Type SDIS SLIM 0.6X3.5X100 Order No. 2749610000

GTIN (EAN) 4050118896350

Qty. 1 pc(s).

Version

Mounting tool, Blade width (B): 3.5 mm, Blade length: 100 mm, Blade

thickness (A): 0.6 mm

A-Series



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

Туре	ATPG 2.5 MI-R	Version
Order No.	<u>1991960000</u>	Test adapter (terminal), 1.5 mm², 250 V, 0.2 A
GTIN (EAN)	4050118376685	
Qty.	50 pc(s).	
Туре	ATPG 1.5-10 L	Version
Order No.	<u>1991890000</u>	Test adapter (terminal), 1.5 mm², 250 V, 0.2 A
Order No. GTIN (EAN)	<u>1991890000</u> 4050118376647	Test adapter (terminal), 1.5 mm², 250 V, 0.2 A



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General	ordering data	
Туре	WS 10/5 MC NE GE	Version
Order No.	<u>1773531687</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141753	Allen-Bradley, yellow
Qty.	720 pc(s).	
Туре	WS 10/5 MC NE RT	Version
Order No.	<u>1773531686</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141746	Allen-Bradley, red
Qty.	720 pc(s).	
Туре	WS 10/5 PLUS MC NE WS	Version
Order No.	1046380000	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248782086	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/5 MC NE BL	Version
Order No.	<u>1773531693</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248141814	Allen-Bradley, blue
Qty.	720 pc(s).	
Туре	WS 10/5 MC NE WS	Version
Order No.	<u>1635000000</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190261948	Allen-Bradley, white
Qty.	720 pc(s).	
Туре	WS 10/5 M PLUS MC NE WS	Version
Order No.	<u>2003770000</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4050118424447	Allen-Bradley, white
Qty.	600 pc(s).	
Туре	WS 10/5 M MC NE WS	Version
Order No.	<u>1792000000</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248223862	Allen-Bradley, white
Qty.	720 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	WS 8/5 MC SDR	Version
Order No.	<u>1640750000</u>	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190456627	Allen-Bradley, To customer specification
Qty.	144 pc(s).	
Туре	WS 8/5 PLUS MC SDR	Version
Order No.	1038790000	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
Order No. GTIN (EAN)	1038790000 4032248768066	WS, Terminal marker, 8 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, Allen-Bradley, To customer specification



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

V0



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 DEK 5/5 MC NE V0 WS
 Version

 Order No.
 1388530000
 Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

 GTIN (EAN)
 4050118188622
 Weidmueller, white

 Oty.
 1,000 pc(s).

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	WS 10/5 MC M SDR	Version
Order No.	<u>1792010000</u>	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248223879	Allen-Bradley, To customer specification
Qty.	144 pc(s).	
Туре	WS 10/5 MC SDR	Version
Type Order No.	WS 10/5 MC SDR 1635010000	Version WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Creation date May 11, 2025 10:10:09 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	WS 10/5 PLUS MC SDR	Version
Order No.	1046320000	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4032248782024	Allen-Bradley, To customer specification
Qty.	120 pc(s).	
Туре	WS 10/5 M PLUS MC SDR	Version
Order No.	2007770000	WS, Terminal marker, 10 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
		Tro, reminar market, re x e min, rest in min (r).
GTIN (EAN)	4050118393279	Allen-Bradley, To customer specification

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

	oraoring aata	
Туре	DEK 5/5 MC NE BL	Version
Order No.	<u>1609801693</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397166	Weidmueller, blue
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE GN	Version
Order No.	<u>1609801688</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397142	Weidmueller, green
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE WS	Version
Order No.	1609801044	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1,000 pc(s).	
Туре	DEK 5/5 S MC NE WS	Version
Order No.	1341620000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118145793	Weidmueller, white
Qty.	400 pc(s).	
Туре	DEK 5/5 MC NE VI	Version
Order No.	1249860000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118042764	Weidmueller, violet
Qty.	1,000 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	DEK 5/5 MC NE RT	Version
Order No.	1609801686	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397128	Weidmueller, red
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE SW	Version
Order No.	<u>1457550000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118263817	Weidmueller, black
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE BR	Version
Order No.	1249870000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118051865	Weidmueller, brown
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE GE	Version
Order No.	<u>1609801687</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397135	Weidmueller, yellow
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE GR	Version
Order No.	<u>1609801691</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397159	Weidmueller, grey
Qty.	1,000 pc(s).	
Туре	DEK 5/5 MC NE OR	Version
Order No.	1238340000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118062632	Weidmueller, orange
Qty.	1,000 pc(s).	

Slotted screwdriver



Slotted screwdriver with rounded blade SD DIN 5265, ISO 2380/2, output to DIN 5264, ISO 2380/1. ChromTop tip, SoftFinish grip

Туре	SDS 1.0X5.5X150	Version
Order No.	<u>2749380000</u>	Screwdriver, Blade width (B): 5.5 mm, Blade length: 150 mm, Blade
GTIN (EAN)	4050118895605	thickness (A): 1 mm
Qty.	1 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/5 PLUS MC NE WS	Version
Order No.	1854490000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4032248393596	Weidmueller, white
Qty.	1,000 pc(s).	
Туре	DEK 5/5 PLUS MC NE GE	Version
0 1 11		
Order No.	<u>1907520000</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	<u>1907520000</u> 4032248532100	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, yellow



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

WS 8/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Туре	WS 8/5 MM WS	Version
Order No.	2007150000	WS, Terminal marker, 8 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392029	
Qty.	800 pc(s).	

2.5 mm²

2.5

The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

Туре	ZQV 2.5N/8	Version
Order No.	<u>1527670000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
GTIN (EAN)	4050118448405	8, Pitch in mm (P): 5.10, Insulated: Yes, Width: 38.5 mm
Qty.	20 pc(s).	
Туре	ZQV 2.5N/10	Version
Type Order No.	ZQV 2.5N/10 1527690000	Version Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
• •	,	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Order No. 1827590000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTN (EAN) 4050118448443 4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm Ory. 60 pc(s). Type 20V 2 EN/7 Version Order No. 1527640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GIN (EAN) 4050118448412 7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm Ory. 20 pc(s). Type ZOV 2.5N/50 Version Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 40501184113362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 256 mm Type ZOV 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Type ZOV 2.5N/2 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width:	Туре	ZQV 2.5N/4	Version
Oity. 60 pc(s). Type ZOV 2.5N/7 Version Order No. 1527640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448412 7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118411362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Type ZOV 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Oity. 20 pc(s). Type ZOV 2.5N/2 Version Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 40501184484867 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 2.3.2 mm Type ZOV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 40501184484363 5, Pitch in mm (P): 5.10, Insulated: Yes, W	Order No.	<u>1527590000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZOV 2.5N/7 Version Order No. 152/7640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448412 7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm Type 20V 2.5N/50 Version Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 405011841362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Oty 5 pc(s). Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty 60 pc(s). Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Type 20V 2.5N/3 Version Ord	GTIN (EAN)	4050118448443	4, Pitch in mm (P): 5.10, Insulated: Yes, Width: 18.1 mm
Order No. 1527640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448412 7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm Oty 20 pc(s). Version Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118411362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Type 20V 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Type 20V 2.5N/2 Version Order No. 1527640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Order No. 1527640000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 405011848436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 40	Qty.	60 pc(s).	
GTIN (EAN) 4050118448412 7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm Ory. 20 pc(s). Type ZOV 2.5N/50 Version Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118411362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118447972 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Order No. 1527670000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 405011844996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A. Number of poles: GTIN (EAN) 405011848429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/7	Version
Qty, 20 pc(s). Type ZOW 2.5N/50 Version Order No. 1527730000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTINI (EAN) 4050118411362 50. Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Oty. 5 pc(s). Type 20V 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTINI (EAN) 4050118447972 20. Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oy. 20 pc(s). Type 20V 2.5N/3 Version Order No. 1527650000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 405011844845	Order No.	<u>1527640000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type	GTIN (EAN)	4050118448412	7, Pitch in mm (P): 5.10, Insulated: Yes, Width: 33.4 mm
Order No. 152773000Q Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118411362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Oty. 5 pc(s). Type ZOV 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Type ZOV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527670000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm <t< td=""><td>Qty.</td><td>20 pc(s).</td><td></td></t<>	Qty.	20 pc(s).	
GTIN (EAN) 4050118411362 50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm Oty. 5 pc(s). Type ZOV 2.5N/20 Version Order No. 1527720000 Order No. 152762000 Order No. 152762000 Order No. 152762000 Order No. 152763000 Order No.	Туре	ZQV 2.5N/50	Version
Qty. 5 pc(s). Type ZOV 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Oty. 20 pc(s). Version Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Type ZOV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 <td>Order No.</td> <td><u>1527730000</u></td> <td>Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:</td>	Order No.	<u>1527730000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZOV 2.5N/20 Version Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Qty. 20 pc(s). Type ZOV 2.5N/2 Version Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Type 20V 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Qty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527670000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN)	GTIN (EAN)	4050118411362	50, Pitch in mm (P): 5.10, Insulated: Yes, Width: 255 mm
Order No. 1527720000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Order No. 527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Order No. 60 pc(s). Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Type ZOV 2.5N/6 Version Order No. <t< td=""><td>Qty.</td><td>5 pc(s).</td><td></td></t<>	Qty.	5 pc(s).	
GTIN (EAN) 4050118447972 20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm Oty. 20 pc(s). Type ZQV 2.5N/2 Version GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Type ZQV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZQV 2.5N/3 Version Order No. 1527670000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZQV 2.5N/3 Version Other No. 1527670000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/20	Version
Qty. 20 pc(s). Type ZQV 2.5N/2 Version Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Qty. 60 pc(s). Type ZQV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Qty. 20 pc(s). Type ZQV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Nu	Order No.	<u>1527720000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZOV 2.5N/2 Version Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Type ZOV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 Yersion Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	GTIN (EAN)	4050118447972	20, Pitch in mm (P): 5.10, Insulated: Yes, Width: 102 mm
Order No. 1527540000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZQV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Otyc. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 </td <td>Qty.</td> <td>20 pc(s).</td> <td></td>	Qty.	20 pc(s).	
GTIN (EAN) 4050118448467 2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm Oty. 60 pc(s). Type ZOV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZOV 2.5N/6 Version Oty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s).	Туре	ZQV 2.5N/2	Version
Oty. 60 pc(s). Type ZQV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZQV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Order No.	<u>1527540000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZQV 2.5N/5 Version Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Qty. 20 pc(s). Type ZQV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Qty. 60 pc(s). Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	GTIN (EAN)	4050118448467	2, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7.9 mm
Order No. 1527620000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Qty. 60 pc(s). Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Qty.	60 pc(s).	
GTIN (EAN) 4050118448436 5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/5	Version
Oty. 20 pc(s). Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Order No.	<u>1527620000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZOV 2.5N/3 Version Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Order No. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	GTIN (EAN)	4050118448436	5, Pitch in mm (P): 5.10, Insulated: Yes, Width: 23.2 mm
Order No. 1527570000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Qty. 60 pc(s). Version Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Qty.	20 pc(s).	
GTIN (EAN) 4050118448450 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm Qty. 60 pc(s). Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/3	Version
Oty. 60 pc(s). Type ZOV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Order No.	<u>1527570000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZQV 2.5N/9 Version Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZQV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	GTIN (EAN)	4050118448450	3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 13 mm
Order No. 1527680000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Qty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Qty.	60 pc(s).	
GTIN (EAN) 4050118447996 9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm Oty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/9	Version
Oty. 20 pc(s). Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Order No.	<u>1527680000</u>	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Type ZOV 2.5N/6 Version Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	GTIN (EAN)	4050118447996	9, Pitch in mm (P): 5.10, Insulated: Yes, Width: 43.6 mm
Order No. 1527630000 Cross-connector (terminal), Plugged, orange, 24 A, Number of poles: GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Qty.	20 pc(s).	
GTIN (EAN) 4050118448429 6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm	Туре	ZQV 2.5N/6	Version
	Order No.	1527630000	Cross-connector (terminal), Plugged, orange, 24 A, Number of poles:
Oty. 20 pc(s).	GTIN (EAN)	4050118448429	6, Pitch in mm (P): 5.10, Insulated: Yes, Width: 28.3 mm
	Qty.	20 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	DEK 5/5 MC SDR	Version
Order No.	1609810000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190456597	Weidmueller, To customer specification
Qty.	200 pc(s).	
Туре	DEK 5/5 PLUS MC SDR	Version
Order No.	1854500000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4032248393602	Weidmueller, To customer specification
Qty.	200 pc(s).	
Туре	DEK 5/5 S MC SDR	Version
Order No.	1341590000	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4050118146042	Weidmueller, To customer specification
Qty.	80 pc(s).	

A-Series



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Type AEB 35 SC/1 BK Version

Order No. 2475310000 A-series, End bracket

GTIN (EAN) 4050118487114

Qty. 50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	AEB 35 SC/1	Version
Order No.	1991920000	A-series, End bracket
GTIN (EAN)	4050118376722	
Qty.	50 pc(s).	
Туре	AEB 35 SCL/1 V0	Version
Order No.	<u>2661280000</u>	A-series, End bracket
GTIN (EAN)	4050118702163	
Qty.	20 pc(s).	
Туре	AEB 35 SCL/1 VO BK	Version
Order No.	<u>2661300000</u>	A-series, End bracket
GTIN (EAN)	4050118702187	
Qty.	20 pc(s).	
Time		
Туре	AEB 35 SCL/1 V0 GY	Version
Order No.	AEB 35 SCL/1 V0 GY 2661290000	Version A-series, End bracket

A-Series



Warning covers with a flash symbol provide more safety for man and machine. They are used where external voltage must be indicated within the application.

Туре	AAM 2.5 YE FLASH	Version
Order No.	<u>2635550000</u>	Terminal marker, 8 x 5.1 mm, Pitch in mm (P): 5.00 yellow
GTIN (EAN)	4050118674095	
Qty.	40 pc(s).	