Product data sheet Characteristics

KBB40ZFPU

Spring fixing bracket, Canalis KBB, 25/40A, adjustable threaded rod suspension system, M6





Main	
Range of product	Canalis
Product or component type	Bracket
Product compatibility	KBB KBA
Fixing device mounting	Suspended on threaded rod
Maximum load	50 kg
Quantity per set	Set of 10

Complementary

Accessory / separate part categor	Fixing accessory
Width	55 mm
Depth	22 mm
Height	266.5 mm
Net weight	160 g

Environment

Standards	IEC 61439-6	
	IEC 60439-2	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	3.200 cm
Package 1 Length	26.700 cm
Package 1 Weight	124.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.000 cm
Package 2 Width	19.500 cm
Package 2 Length	29.000 cm
Package 2 Weight	1.240 kg
Unit Type of Package 3	P06
Number of Units in Package 3	400
Package 3 Height	76.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	56.600 kg

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product	
REACh Regulation	☑REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
Sustainable packaging	Yes	
China RoHS Regulation	[☑] China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
PVC free	Yes	
Halogen content performance	Halogen free product	

18 months

KBB40ZFPU

