PKY32M735

Wander socket outlet, Mureva PK, Fast connection, 32A, 3P+N+E, 400V, IP67





Main

| Range | Mureva |
|---------------------------|---------------|
| Product or component type | Wander socket |
| Device short name | Mureva fast |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| Complementary | | |
|-------------------------------------|---|--|
| Plug, socket, control station shape | Straight | |
| [In] rated current | 32 A | |
| [Ue] rated operational voltage | 380415 V | |
| Network frequency | 50/60 Hz | |
| Ground lug clockwise position | 6 h | |
| Plug, socket material | Housing: self-extinguishing engineering polymer | |
| Contacts material | Sleeves: brass | |
| Connections - terminals | Fast connection | |
| Cable cross section | 2.56 mm² | |
| Cable outer diameter | 11.521 mm | |
| Cable entry | Cable gland | |
| Thread type | Pg 21 | |
| Net weight | 0.361 kg | |
| Height | 104 mm | |
| Width | 104 mm | |
| Depth | 173 mm | |
| Colour | Grey (RAL 7035) | |
| Voltage colour | Red | |
| | | |

Environment

| Standards | IEC 60309-1 | |
|---------------------------------------|------------------------------------|--|
| | IEC 60309-2 | |
| IP degree of protection | IP67 conforming to IEC 60529 | |
| IK degree of protection | IK08 conforming to EN 62262 | |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 | |
| Relative humidity | 50 % at 40 °C | |
| | 70 % at 30 °C | |
| | 90 % at 20 °C | |
| Ambient air temperature for operation | 35 °C (86400 s) | |
| | -2540 °C | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.000 cm |
| Package 1 Width | 10.000 cm |
| Package 1 Length | 17.500 cm |
| Package 1 Weight | 330.400 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 17.500 cm |
| Package 2 Width | 26.500 cm |
| Package 2 Length | 26.500 cm |
| Package 2 Weight | 2.136 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 12 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 4.703 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | ☑ REACh Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | ☐ China RoHS Declaration |
| RoHS exemption information | ₽¥Yes |
| Environmental Disclosure | ☑ Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|