
WIN PRO+ 30 S/EW ZHAGA

Part number 3116199







IP 66 | CLASS I | ≤-40°C | FULL CUT OFF | ULR<1 | CIEn°3>95 | SPD 10kV

Description

LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Coated die-cast aluminium captive trim, hinged to the housing
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- Complete with 1 m factory pre-wired cable H07RN-F 3G1.5 mm^2
- Stainless steel locking hardware
- Powder-coated steel tiltable bracket
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- Complete with ZHAGA socket positioned on the upper part of the luminaire (UP position) and D4i driver. Ready for "radio frequency node" smart, twilight and other compatible solutions (ZHAGA options). Consult factory for more options
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001744

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	40613	**Luminaire lumen output [lm]:**	37879
Luminaire wattage [W]:	252 W	**Luminous efficacy [lm/W]:**	150
CRI:	70	**Colour temperature [K]:**	3000
Colour / Finishing:	GR-94 / Metallic grey / Textured	**IP degree of protection:**	IP66
Impact resistance / impact energy:	IK08 5J xx5	**Protection class:**	I
Optic:	S/EW - Symmetric Extra-Wide	**Net weight [kg]:**	10.088
Overall length [mm]:	411	**Overall width [mm]:**	528
Overall height [mm]:	95		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Glass	**Glow wire test [°C]:**	960 °C
Frontal exposed area [m²]:	0.03	**Lateral exposed area [m²]:**	0.04
Top exposed area [m²]:	0.18		

Electrical features

Voltage type:	AC/DC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	0/50/60	**Power factor / COS Φ:**	>0.9
Input voltage [V DC]:	176/280	**Surge protection | Common [kV]:**	10.000000
Surge protection | Differential [kV]:	10.000000	**Inrush current [A/µs]:**	112 / 554
C10 1.5 mm²:	1	**C16 2.5 mm²:**	2
B10 1.5 mm²:	2	**B16 2.5 mm²:**	4

Installation

Application area:	Outdoor lighting	**Mounting type:**	Professional floodlight
Min. ambient temperature [°C]:	-40	**Max. ambient temperature [°C]:**	40
Min. distance from lighted object [m]:	0.50		

Light features

MacAdam:	3	**Lumen maintenance:**	L80B10@190000h
Distribution of light emission:	Direct	**Luminous Intensity Class:**	G*6
Zero light pollution (ULR = 0%):		**IPEA* (road lighting):**	A4+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com


IPEA* (large areas, roundabouts):	A9+	**IPEA* (cycle-pedestrian):**	A5+
IPEA* (green areas):	A5+	**IPEA* (historic city centers):**	A10+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories


WIN PRO 30



14045794

External steel cowl painted aluminium grey

GR-94 / Metallic grey



14045694

External anti-glare louvre painted aluminium grey

GR-94 / Metallic grey



14046120

Strengthening bracket. Suitable for one floodlight single point fixing M12 screw in centre of the bracket


INOX / Stainless steel



14051294

Single pole top mounting, for Ø 60-76 mm poles, painted aluminium grey

GR-94 / Metallic grey



14048694

1000 mm extension arm in heavy gauge steel, painted aluminium grey

GR-94 / Metallic grey



14051394

Double pole top mounting, Ø 60-76 mm poles, painted aluminium grey

GR-94 / Metallic grey

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com



14057394

Long bracket for ceiling mounting, painted aluminium grey

GR-94 / Metallic grey



3115887

Connection Kit 5P Ø 8÷17 mm - IP68

-9999

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com