Busbar terminal

# SKLAL 135



## SKLAL 135

**Busbar terminal**

Productnumber: 07613501
Dimensions: 16 x 26,5 x 36 mm

Busbar terminal, for copper rails 12/20/25/30 x 10 mm

**for connection of AL/CU conductors 4-35mm²**

35²

# Technical Data

## electrical characteristics

| | |
|---|---|
| Max. conductor cross section: | 35 mm² |
| Rated current: | 270 A |
| Number of poles: | 1 |
| shockproof: | No |
| Connection 1: Connection type: | Screws |
| Connection 1: Clamping points per pole: | 1 |
| Connection 1: Suitable for Cu conductors: | 1 |
| Connection 1: Suitable for Al conductors: | 1 |
| Connection 1: Connectable conductor cross-section, single-wire (min): | 4 mm² |
| Connection 1: Connectable conductor cross-section, single-wire (max): | 35 mm² |
| Connection 1: Connectable conductor cross-section, stranded (min): | 4 mm² |
| Connection 1:Connectable conductor cross-section, stranded (max): | 35 mm² |

## Dimensions

| | |
|---|---|
| Width: | 16 mm |
| Length: | 26.5 mm |
| Height: | 36 mm |
| Weight: | 0.0254 kg |

## mechanical properties

| | |
|---|---|
| Connection 1: Tightening moment: | 6 Nm |

## Sales Information

| | |
|---|---|
| EAN: | 4013902623013 |
| ETIM Class: | EC000001 |
| Custom tariff number: | 85369010 |
| Minimum order quantity: | 1 |