

KNT63AB4

End feed unit, Canalis KNT, 40/63A, right or left mounting, 3L+N+PE/3L+PEN, with built-in transmission bus, RAL9001



Main

Range of product	Canalis
Product name	KN
Device short name	KNT
Product compatibility	Canalis KNT busbar trunking 40...63 A
Product or component type	Feed unit
Conductors material	Aluminium
[Ie] rated operational current	63 A
[Ue] rated operational voltage	230...500 V
Number of circuits	1
Protection type	Without protection
Control type	Remote control
Colour	White (RAL 9001)

Complementary

Provided equipment	End cover
Mounting location	Left Right
Mounting mode	By clips
Mounting support	Busbar
Connections - terminals	Terminal block for 16 mm ² flexible Terminal block for 25 mm ² rigid
Width	265 mm
Depth	71 mm
Height	92 mm
Net weight	580 g
Standards	IEC 61439-6

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	10.5 cm
Package 1 Length	30.0 cm
Package 1 Weight	680.0 g
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	36.0 cm
Package 2 Width	80.0 cm

Package 2 Length	60.0 cm
Package 2 Weight	9.128 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------