


date: 23/10/2026

INSERT+ ZERO POST 300

Part number 3118124







IP 65 | CLASS I | CE | EAC | UKCA

Description

Post mounted outdoor luminaire for general lighting, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Anti-ageing custom moulded silicone sealing gasket(s)
- Extruded aluminium post with base plate, polyester powder coat finish
- Rapid spring-type installation
- No visible screws

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC000301

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	435	**Luminaire lumen output [lm]:**	148
Luminaire wattage [W]:	4 W	**Luminous efficacy [lm/W]:**	37
CRI:	80	**Colour temperature [K]:**	2700
Colour / Finishing:	AN-96 / Anthracite gray / Textured	**IP degree of protection:**	IP65
Impact resistance / impact energy:	IK08 5J xx5	**Protection class:**	I
Optic:	A/W - Asymmetric Wide	**Net weight [kg]:**	1.801
Overall length [mm]:	130	**Overall width [mm]:**	53
Overall height [mm]:	305		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Opal glass		

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	0.8
Inrush current [A/µs]:	4 / 414	**C10 1.5 mm²:**	160
C16 2.5 mm²:	256	**B10 1.5 mm²:**	100
B16 2.5 mm²:	160		

Installation

Application area:	Outdoor lighting	**Mounting type:**	Garden post
Min. ambient temperature [°C]:	-20	**Max. ambient temperature [°C]:**	40

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@65000h
Distribution of light emission:	Direct	**DFF - Downward Flux Fraction [%]:**	97
UFF - Upward Flux Fraction [%]:	3	**Luminous Intensity Class:**	G*1

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com