

SL629+ SM S/B

Part number LTX12G4DQ801







IP 20 | CLASS I | MULTI WHITE | DALI | TOUCH | CE | UKCA

Description

LED surface-mount luminaire for indoor, comprising:
- Steel sheet housing, die-cast aluminium end caps, polyester powder coat finish
- Prismatic diffuser for efficient light distribution, glare reduction and a high level of uniformity
- FUTURE-PROOF = replaceable light engine and components
- Maintenance and installation-friendly design (complies with the EU Eco-Design Directive 2019/2020)
- LED Sidelight-Technology for a homogenous light distribution over the entire area of the cover
- Direct/indirect light spread (corona for subdued ceiling lightening)
- Glare-free light for office applications in accordance with DIN EN 12464-1 (UGR<19 and <3000cd/m^2 >65°)
- Flexible power level setting via DIP switch (50 / 75 / 100%)
- Dip switch for LED CCT control at 3000K or 4000K, field adjustable
- Suitable for sustainable 1:1 replacement - no extensive ceiling work necessary
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Maximum values for efficiency and service life for the allocation of subsidies and building certification (e.g. BEG subsidy, LEED, BREEAM)
- Produced in Germany - with a focus on quality, short delivery routes and low environmental impact
- Effortless upgrade: sensor modules can be integrated at any time via plug-and-play
- Casambi control available as an accessory
- Through-wiring designed
- Special colour versions available. Consult factory

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC002892

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	9300	**Luminaire lumen output [lm]:**	6760
Luminous efficacy [lm/W]:	138	**CRI:**	80
Colour temperature [K]:	3000/4000	**Colour / Finishing:**	WH-RAL9016 / White RAL9016 / Textured
IP degree of protection:	IP20	**Impact resistance / impact energy:**	IK05 0.7J xx3
Protection class:	I	**Optic:**	S/B - Symmetric mainly direct
Beam angle:	2 x 36°/47°	**Net weight [kg]:**	8.021
Overall length [mm]:	1244	**Overall width [mm]:**	275
Overall height [mm]:	50		

Mechanical features

Shape:	Rectangular	**Diffuser material:**	Transparent plastic
Glow wire test [°C]:	650 °C		

Electrical features

Voltage type:	AC/DC	**Input voltage [V AC]:**	200/240
Input frequency [Hz]:	220-240V 0/50/60Hz	**Power factor / COS Φ:**	>0.9

Installation

Application area:	Indoor lighting	**Mounting type:**	Wall and ceiling surface
Min. ambient temperature [°C]:	10	**Max. ambient temperature [°C]:**	40

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@50000h
Distribution of light emission:	Direct/Indirect	**DFF - Downward Flux Fraction [%]:**	98
UFF - Upward Flux Fraction [%]:	2	**UGR max.:**	22.0

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories

SL629+ SM




LTX1A1550

Mounting kit for continuous-row lighting system for surface-mounted luminaire


SMART accessories

SL629+ SM



3122584

Casambi module for installation



3122586

Single wireless wall switch


☐ WH-87 / White



3122587

Double wireless wall switch

☐ WH-87 / White



8118000257


Remote control "Master" for versions with a sensor function

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

date: 27/10/2026



LTX1A6115

Sensor Modules Standalone

☐ WH-RAL9016 / White RAL9016

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com