

VPU PV I+II 5 1500**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Abb. ähnlich

General ordering data

Order No.	3012980000
Type	VPU PV I+II 5 1500
GTIN (EAN)	4099986922587
Qty.	1 pc(s).

VPU PV I+II 5 1500

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	86 mm	Depth (inches)	3.386 inch
Height	96.5 mm	Height (inches)	3.799 inch
Width	90 mm	Width (inches)	3.543 inch
Net weight	760 g		

Temperatures

Storage temperature	-40 °C...85 °C	Ambient temperature	-40 °C...85 °C
Operating temperature	-40 °C...85 °C	Humidity	5 - 95% rel. humidity

General data

Number of poles	5	Protection degree	IP20 in installed state
Colour	orange, black		

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	I, III
--------------------	---	------------------------	--------

Photovoltaic technical data

Discharge current I_n (8/20 μ s)	20 kA	Lightning test current I_{imp} (10/350 μ s)	5 kA
Operating height in the grounded PV system	≤ 2000 m	Operating height in ungrounded PV system	≤ 4000 m
PV system voltage, max. U_{cpv}	1,500 V	Protection level U_p (+/-, -/PE, +/PE)	$\leq 5,0$ kV
Protection level U_p (+/-)	$\leq 5,0$ kV	Short-circuit current I_{SCP}	11,000 A
Standards	EN 61643-31, EN 50539-11	Total discharge current I_{total} (8/20 μ s)	50 kA
Total discharge current I_{total} (10/350 μ s)	10 kA		

Rated data IEC / EN

Discharge current I_{max} (8/20 μ s) wire-PE	30 kA	Integrated back-up fuse	No
Leakage current at U_n	30 μ A	Lightning test current I_{imp} (10/350 μ s)	5 kA
Max. continuous voltage, U_c (DC)	1500 V	Number of poles	5
Rated voltage (DC)	1500 V	Response time	≤ 25 ns
SPD type	T2, T1	Short-circuit current rating I_{SCCR}	50 kA
Signalling contact	No	Standards	EN 61643-31, EN 50539-11
Suitable for	Photovoltaics	Voltage type	DC

Connection data

Stripping length	18 mm	Wire connection method	Screw connection
Stripping length, rated connection	18 mm	Tightening torque, min.	3 Nm
Tightening torque, max.	4.5 Nm	Clamping range, rated connection	6 mm ²
Clamping range, min.	1.5 mm ²	Clamping range, max.	35 mm ²
Wire cross-section, solid, min.	1.5 mm ²	Wire cross-section, solid, max.	35 mm ²
Wire connection cross section, finely stranded, max.	25 mm ²	Connection cross-section, stranded, min.	1.5 mm ²
Connection cross-section, stranded, max.	35 mm ²		

VPU PV I+II 5 1500

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Electrical data

Voltage type	DC
--------------	----

Guarantee

Time interval	5 years
---------------	---------

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
ETIM 8.0	EC000941	ETIM 9.0	EC000941
ETIM 10.0	EC000941	ECLASS 9.0	27-13-08-05
ECLASS 9.1	27-13-08-05	ECLASS 10.0	27-13-08-05
ECLASS 11.0	27-13-08-05	ECLASS 12.0	27-17-90-90
ECLASS 13.0	27-17-90-90	ECLASS 14.0	27-17-90-90
ECLASS 15.0	27-17-90-90		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
------------------------	-----------------------------

REACH SVHC	No SVHC above 0.1 wt%
------------	-----------------------

Approvals

Approvals



Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/
-----------------	---

ROHS	Conform
------	---------

Downloads


Approval/Certificate/Document of Conformity	CE VPU PV I+II 5_pole
Engineering Data	CAD data – STEP
User Documentation	Beipackzettel / Instruction Sheet
Catalogues	Catalogues in PDF-format

VPU PV I+II 5 1500

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings




VPU PV I+II 5 1500**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Accessories****Slotted screwdriver**

VDE insulated slot-head screwdriver, SDI DIN 7437, ISO 2380/2, drive output acc. to DIN 5264, ISO 2380/1. SoftFinish grip

General ordering data

Type	SDIS 1.0X5.5X125	Version
Order No.	2749850000	Screwdriver, Blade width (B): 5.5 mm, Blade length: 125 mm, Blade
GTIN (EAN)	4050118897050	thickness (A): 1 mm
Qty.	1 pc(s).	

Spare Arrester**General ordering data**

Type	VPU PV I+II 5 0 1500
Order No.	3013020000
GTIN (EAN)	4099986922617
Qty.	1 pc(s).

Type	VPU PV I+II 5 0M 1500
Order No.	3013010000
GTIN (EAN)	4099986922600
Qty.	1 pc(s).