

KSC400ED4081

Vertical distribution length, Canalis KSC400, copper, 400A, fixed length 0.8m, 1 outlet, 3L+N+PE/3L+PE, white RAL9001



Main

Range	Canalis
Device short name	KSC
Product or component type	Busbar trunking
Busbar description	Vertical distribution length
Product compatibility	Canalis KSC busbar trunking 400 A
Conductors material	Copper
Busbar trunking polarity	3L + N + PE 3L + PE
Number of tap-off outlets	1
[Ie] rated operational current	400 A at 35 °C
IP degree of protection	IP55 conforming to IEC 60529
Mounting mode	By screws
Dimension type	Fix
Length	0.8 m
Colour	White (RAL 9001)

Complementary

Number of poles	4
Neutral position	Right
Mounting support	Foot riser
Mounting position	Vertical
[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	18.8 kA
[Ipk] rated peak withstand current	49.2 kA
Electrical connection	Lubricated sliding contact
Width	54 mm
Height	146 mm
Net weight	9 kg
Radiated magnetic field	1 µT
Thermal stress limit	354000 kA².s
THDI	0...15 % 400 A 15...33 % 315 A 33...100 % 250 A
Maximum voltage drop	<0.0184 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0179 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0177 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0176 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Standards	IEC 61439-1 IEC 61439-6

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.


Environment

IK degree of protection	IK08 conforming to IEC 62262
Ambient air temperature for operation	35 °C (without derating) 55 °C (with derating factor)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	16.7 cm
Package 1 Length	88.85 cm
Package 1 Weight	11 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product