

**RCL425024T****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Similar to illustration

**General ordering data**

Version	, Relay, Number of contacts: 2, CO contact AgNi, Rated control voltage: 24 V DC $\pm 10\%$ , Continuous current: 8 A, Plug-in connection
Order No.	<a href="#">2494270000</a>
Type	RCL425024T
GTIN (EAN)	4050118517507
Qty.	20 items

## RCL425024T

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

### Approvals

ROHS	Conform
------	---------

### Dimensions and weights

Depth	29 mm	Depth (inches)	1.1417 inch
Height	15.7 mm	Height (inches)	0.6181 inch
Width	12.7 mm	Width (inches)	0.5 inch
Net weight	13.3 g		

### Temperatures

Storage temperature	Ambient temperature	-20 °C...70 °C
Operating temperature		

### Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

### Control side

Rated control voltage	24 V DC ±10 %	Status indicator	No
-----------------------	---------------	------------------	----

### Load side

Continuous current	8 A	Max. switching voltage, AC	250 V
Min. switching current	5 mA	Contact type	2 CO contact (AgNi)

### Insulation coordination

Protection degree	IP40
-------------------	------

### Connection data

Wire connection method	Plug-in connection
------------------------	--------------------

### Classifications

ETIM 8.0	EC001437	ETIM 9.0	EC001437
ETIM 10.0	EC001437	ECLASS 14.0	27-37-16-01
ECLASS 15.0	27-37-16-01		