

Data sheet

KRZ-E08 HR 24 V AC/DC

Page 1/6

P/N

110668132722

EAN 4250184122982


2026/09/22

Version: L


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

The coupling module is designed for two-level motor control.

- Connection with screw type terminal blocks
- Interlocked relays
- Manual control level

Data sheet

KRZ-E08 HR 24 V AC/DC

Page 2/6

P/N
110668132722
EAN 4250184122982
2026/09/22
Version: L

Technical Data

Supply

Operating voltage	24 V AC/DC -10% ... +10%
Power consumption (max.)	30 mA
Current per terminal (max.)	4 mA
Response time typical	20 ms
Release time typical	20 ms
Time delay stage 2 to stage 1	< 60 ms

Manual control level

Mechanical life	3x10 ⁴ switchings
Switching capacity (max.)	24 V AC/DC / 1 A
Test voltage	2000 V AC, 50 Hz, 1 min.

Outputs

Contacts	1 changeover contact
Contact material	AgSnO ₂
Switching voltage (max.)	250 V AC
Switch-on current	6 A
Continuous Current	4 A
Switching frequency	1200 switching cycles/h
Breaking capacity (resistive load)	
Mechanical life	1x10 ⁷ switching cycles
Electrical life	1x10 ⁵ switching cycles
Indicator	red LED

Insulation coil - contact set

Nominal voltage of the power supply system	230 / 400 V AC
Overvoltage category	III II
Degree of pollution	2 2
Rated test voltage	4 kV 2.5 kV
Type of insulation	basic insulation reinforced insulation

Data sheet

KRZ-E08 HR 24 V AC/DC

Page 3/6

P/N
110668132722
EAN 4250184122982
2026/09/22
Version: L

Technical Data

Housing

Dimensions

Dimension (W x H x D)	22.5 mm x 61.3 mm x 60 mm
Dimension (W x H x D)	0.886 in. x 2.413 in. x 2.362 in.
Weight	70 g
Mounting style	Standard rail TH35
Mounting position	any
Apposition	without distance
Connection type	Screw type terminal blocks

Terminal blocks

Wire cross section solid	0.34 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section multi	0.25 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section with wire ferrule	0.25 mm ² - 2.5 mm ² / AWG 22-12
Screw torque (max.)	0.5 Nm
Stripping length (min.)	8 mm

Material

Material - Housing	Polyamid 6.6 V0
Color	gray
Material - Terminal block	Polyamid 6.6 V0

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
Protection category - terminal blocks (acc. to IEC 60529)	IP20

Climatic Data

Operating	
Temperature - Operating °C	-20 °C - 55 °C
Temperature - Operating °F	-4 °F - 131 °F
Relative humidity	max. 85 % non-condensing
Storage	
Temperature - Storage °C	-25 °C - 70 °C
Temperature - Storage °F	-13 °F - 158 °F

Data sheet
KRZ-E08 HR 24 V AC/DC

Page 4/6

P/N
110668132722
EAN 4250184122982
2026/09/22
Version: L

Technical Data

Power loss

Power loss (typical) 1 W

Classifications

ETIM 7.0	EC001437
ETIM 8.0	EC001437
ETIM 9.0	EC001437
ETIM 10.0	EC001437

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.


Data sheet
KRZ-E08 HR 24 V AC/DC

Page 5/6

P/N
110668132722
EAN 4250184122982
 2026/09/22
 Version: L

Illustrations

Dimensional drawing



Wiring diagram

A1	B1	B2	A2
24	11	14	S

A1 - A2
 operating voltage
 24 V AC/DC
B1 - B2
 control inputs
 11 - 14 - 24
 output contact
 1 changeover
S
 manual checkback
 function




Data sheet
KRZ-E08 HR 24 V AC/DC

Page 6/6

P/N
110668132722
EAN 4250184122982
2026/09/22
Version: L

Illustrations

Circuit diagram



Function diagram

