

**ZQV 4N/41 RD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

**General ordering data**

|            |                                                                                                                             |
|------------|-----------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), Plugged, red, 32 A, Number of poles: 41, Pitch in mm (P): 6.10, Insulated: Yes, Width: 253.9 mm |
| Order No.  | <a href="#">2883840000</a>                                                                                                  |
| Type       | ZQV 4N/41 RD                                                                                                                |
| GTIN (EAN) | 4064675848868                                                                                                               |
| Qty.       | 10 pc(s).                                                                                                                   |

**ZQV 4N/41 RD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 28 mm    | Depth (inches)  | 1.102 inch |
| Height     | 2.8 mm   | Height (inches) | 0.11 inch  |
| Width      | 253.9 mm | Width (inches)  | 9.996 inch |
| Net weight | 3.3 g    |                 |            |

**Temperatures**

|                                  |                 |                                  |               |
|----------------------------------|-----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C  | Ambient temperature              | -5 °C...40 °C |
| Operating temperature            | -60 °C...130 °C | Continuous operating temp., min. | -60 °C        |
| Continuous operating temp., max. | 130 °C          |                                  |               |

**Material data**

|                           |       |        |     |
|---------------------------|-------|--------|-----|
| Material                  | Wemid | Colour | red |
| UL 94 flammability rating | V-0   |        |     |

**Additional technical data**

|                          |         |                |         |
|--------------------------|---------|----------------|---------|
| Explosion-tested version | No      | Type of fixing | Plugged |
| Type of mounting         | Plugged |                |         |

**Cross-connector**

|                           |      |      |                 |
|---------------------------|------|------|-----------------|
| Rated current, multi-pole | 32 A | Type | Cross-connector |
|---------------------------|------|------|-----------------|

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

**General**

|                 |    |
|-----------------|----|
| Number of poles | 41 |
|-----------------|----|

**Rating data**

|               |       |               |      |
|---------------|-------|---------------|------|
| Rated voltage | 400 V | Rated current | 32 A |
|---------------|-------|---------------|------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0    | EC000489    |
| ETIM 8.0    | EC000489    | ETIM 9.0    | EC000489    |
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## ZQV 4N/41 RD

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Important note

Product information

Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400V The voltage reduced to 25V if cut cross connection with blank cut edges are used

### Approvals

ROHS

Conform

### Downloads

Engineering Data

[CAD data – STEP](#)