

Data sheet

Page 2/4

OpDAT pre-assembled splice tray 12xLC APC OS2

P/N

150929JA00-E

EAN 4251122185861

2026/09/15

Version: M

Technical Data

General Data

Fields of application	data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	pre-assembled splice tray
Transmission technology	Fiber optic
Color	green
Dimensions	
Dimension (L x W x H)	92 mm x 154.5 mm x 10 mm
Dimension (L x W x H)	3.622 in. x 6.083 in. x 0.394 in.
Mode type of the fiber	Singlemode
Fiber class	OS2 (ISO/IEC 11801/EN50173 & IEC 60793-2-50 B1.3, B6_a & ITU-T G.657.A1, G.652.D)
Cable Type	pigtail(s)
Number of cables/ buffered fibers	12
Shape	APC (Angled Physical Contact)
Fiber construction	9/125 µm
Minimum length	0.8 m
Minimum length	2.62 ft
Maximum length	0.9 m
Maximum length	2.95 ft

Connections/interfaces

Connector technology interface 2	LC APC
----------------------------------	--------

Optical characteristics

Insertion loss	max. 03 dB
Return loss	min. 65 dB



OpDAT pre-assembled splice tray 12xLC APC OS2

P/N

150929JA00-E

EAN 4251122185861

2026/09/15

Version: M

Technical Data

Materials and material properties

Material - Coupler housing	Plastics
Material - Housing	ABS
Halogen free	yes
RoHS	compliant

Standards/Regulations

Generic cabling systems	
General requirements	ISO/IEC 11801
Fibre optic connector interfaces	IEC 61754-20
Optical fibers: Indoor optical cables	
Sectional specification for class B single-mode fibres	ISO/IEC 60793-2-50 type B.1.3 & B6_a
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components - Visual inspection of plug end face	IEC 61300-3-4 IEC 61300-3-6
Standard colours for insulation for low-frequency cables & wires	IEC 60304
ITU-T standard	ITU-T G.657.A1 compatible with ITU-T G.652.D

Classifications

ETIM 7.0	EC000762
ETIM 8.0	EC000762
ETIM 9.0	EC000762
ETIM 10.0	EC000762

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

OpDAT pre-assembled splice tray 12xLC APC OS2

P/N

150929JA00-E

EAN 4251122185861

2026/09/15

Version: M

Illustrations

Dimensional drawing

