


# KHA CITY COMFORT 26 C/EW

## Part number 3114911








### Description

Series of lighting columns, comprising:
- The COMFORT models feature aluminium housing, body and top-cap in polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- The COMFORT options are designed to optimise visual comfort and reduce glare
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- Integral surge protection device (SPD) against mains overvoltages up to 10 kV (CM/DM)
- IP68-rated, loop-through, technopolymer box (WATER-STOP), connected with factory pre-wired H07RN-F cable to the luminaire, for cables Ø 7 - 13.5 mm
- Stainless steel locking hardware
- Bolt-on root galvanised steel plinth or stainless steel flange plate (anchor plugs not included) floor mounting options available as accessories for KHA CITY 26 e KHA CITY COMFORT 26 (ordered separately)

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

**info.it@pil.lighting**
www.performanceinlighting.com

## Product data

| | | | |
|---|---|---|---|
| **ETIM Group:** | EG000027 | **ETIM Class:** | EC000301 |

## General information

| | | | |
|---|---|---|---|
| **Lampholder:** | LED | **Light source:** | LED |
| **Lightsource lumen output [lm]:** | 3335 | **Luminaire lumen output [lm]:** | 2056 |
| **Luminaire wattage [W]:** | 23 W | **Luminous efficacy [lm/W]:** | 89 |
| **CRI:** | 80 | **Colour temperature [K]:** | 4000 |
| **Colour / Finishing:** | BK-81 / Black / Textured | **IP degree of protection:** | IP66 |
| **Impact resistance / impact energy:** | IK10 24J xx9 | **Protection class:** | II |
| **Optic:** | C/EW - Circular Extra-Wide | **Net weight [kg]:** | 14 |
| **Overall diameter [mm]:** | 155 | **Overall height [mm]:** | 2600 |

## Mechanical features

| | | | |
|---|---|---|---|
| **Shape:** | Round ≤ 150 mm | **Housing material:** | Aluminium |
| **Diffuser material:** | Plastic | **Glow wire test [°C]:** | 650 °C |
| **Frontal exposed area [m²]:** | 0.4 | **Lateral exposed area [m²]:** | 0.4 |
| **Top exposed area [m²]:** | 0.02 | | |

## Electrical features

| | | | |
|---|---|---|---|
| **Voltage type:** | AC | **Input voltage [V AC]:** | 220/240 |
| **Input frequency [Hz]:** | 220-240V 0/50/60Hz | **Power factor / COS Φ:** | >0.9 |
| **Surge protection \| Common [kV]:** | 10.000000 | **Surge protection \| Differential [kV]:** | 10.000000 |
| **Inrush current [A/µs]:** | 26 / 180 | **C10 1.5 mm²:** | 29 |
| **C16 2.5 mm²:** | 46 | **B10 1.5 mm²:** | 10 |
| **B16 2.5 mm²:** | 28 | | |

## Installation

| | | | |
|---|---|---|---|
| **Application area:** | Outdoor lighting | **Mounting type:** | Bollard and column |
| **Min. ambient temperature [°C]:** | -25 | **Max. ambient temperature [°C]:** | 50 |
| **Min. distance from lighted object [m]:** | 0.50 | | |

## Light features

| | | | |
|---|---|---|---|
| **MacAdam:** | 5 | **Lumen maintenance:** | L80B10@350000h |
| **Distribution of light emission:** | Direct | **Luminous Intensity Class:** | G*6 |
| **Zero light pollution (ULR = 0%):** | | **IPEA* (road lighting):** | A+ |
| **IPEA* (large areas, roundabouts):** | A+ | **IPEA* (cycle-pedestrian):** | A |
| **IPEA* (green areas):** | A | **IPEA* (historic city centers):** | A3+ |

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


**info.it@pil.lighting**
www.performanceinlighting.com

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


**info.it@pil.lighting**
www.performanceinlighting.com

## Photometric data




## Mandatory accessories

KHA CITY 26



**3114957**

Hot dipped galvanised fixing base for recessing into concrete.



**3114960**

AISI 316 stainless steel floor installation base

INOX / Stainless steel

## Optional accessories

KHA CITY 26



**3115347**

Concrete mounting adaptor with stainless steel plate and galvanised steel rods

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
**PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy**
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

**info.it@pil.lighting**
www.performanceinlighting.com