Main cable junction terminal

HA 25-16



HA 25-16

Main cable junction terminal

Productnumber: 69113201
Dimensions: 22 x 40,7 x 40 mm

Main cable junction terminal with 4 clamping points 25 mm², 1-pole

1-pole finger proof

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	1000 V
Number of poles:	1
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	4
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	25 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	2.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	25 mm²
Connection 2: Connection type:	Screws
Connection 2: Suitable for Cu conductors:	1
Connection 2: Connectable conductor cross-section, single-wire (min):	2.5 mm²
Connection 2: Connectable conductor cross-section, single-wire (max):	16 mm²
Connection 2: Connectable conductor cross-section, stranded (min):	2.5 mm²
Connection 2: Connectable conductor cross-section, stranded (max):	16 mm²

Dimensions

Width:	22 mm
Length:	40.7 mm
Height:	40 mm
Weight:	0.0636 kg

Material characteristics

Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Connection 1: Tightening moment:	2.5 Nm
Connection 2: Tightening torque:	2.5 Nm

Sales Information

EAN:	4013902903825
ETIM Class:	EC000275
Custom tariff number:	85369010
Minimum order quantity:	10