Busbar terminal

SKL 116



SKL 116

Busbar terminal

Productnumber: 07511601
Dimensions: 12 x 25,5 x 31,5 mm

Busbar terminal, for copper rails 12/20/25/30 x 10 mm

for CU conductor 1x (1.5-16 mm²) re/rm/rf+AE

16²

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Max. conductor cross section:	16 mm²
Rated current:	180 A
Number of poles:	1
shockproof:	No
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	1
Connection 1: Suitable for Cu conductors:	1
Connection 1: Suitable for Al conductors:	1
Connection 1: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	16 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	1.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	16 mm²

Dimensions

Width:	12 mm
Length:	25.5 mm
Height:	31.5 mm
Weight:	0.0214 kg

mechanical properties

Connection 1: Tightening moment:	3 Nm

Sales Information

EAN:	4013902051946
ETIM Class:	EC000001
Custom tariff number:	85369010
Minimum order quantity:	1