# Product data sheet Characteristics

# LV432579

Rear insulation screens, ComPacT NSX400/630, 4 poles, pitch 70mm, set of 2 parts



Main	
Product or component type	Insulation screen
Range compatibility	ComPacT new generation ComPacT NSX400 new generation
	ComPacT new generation ComPacT NSX630 new generation
	ComPacT new generation ComPacT NSX DC new generation NSX400 DC
	ComPacT new generation ComPacT NSX DC new
	generation NSX630 DC ComPact ComPact NSX400
	ComPact ComPact NSX630
	ComPact Compact NSX400 DC
	ComPact Compact NSX630 DC
	EasyPact EasyPact CVS400
	EasyPact EasyPact CVS630
Accessory / separate	Insulation accessories
part type	
Poles description	4P
Quantity per set	Set of 2

#### Complementary

Connection pitch	70 mm
Product compatibility	Circuit-breaker

### **Packing Units**

. doming of mo	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.4 cm
Package 1 Width	27.5 cm
Package 1 Length	28.0 cm
Package 1 Weight	281.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	40
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	11.64 kg

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interested for a set of or determining suitability or intelability of these products for specific user applications. It is the documentation is not integrator to perform the appropriate and complete risk analysis, evaluating of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months