

The technical drawing illustrates a metal bracket assembly. On the left, a photograph shows the physical component, which consists of a vertical pipe, a horizontal arm, and a mounting plate. The main drawing includes three views: a front view, a top view, and a side view. The front view shows a horizontal arm with a central diamond-shaped hole and two octagonal holes. The top view shows the arm's profile with a central diamond-shaped hole and two octagonal holes. The side view shows the arm's profile with a central diamond-shaped hole and two octagonal holes. The drawing includes dimensions: 169, 230-400, 40, 4, 120, 220, 40x4, 30x3, 94, 12, 40, and Ø11.4.

Tipo art. no.	WB D40.50 V230.400 STTZN V2A 105 347
Material	St/tZn / INOX
Fijación	[4x] 12 x 26 mm
Distancia a la pared	230-400 mm
Margen de apriete (varilla captadora)	40 / 50 mm
Material del tornillo	INOX mm
Peso	2,42 kg
Número aduanero (Nomenclatura Combinada EU)	85389099
GTIN	4013364278554
UPE	1 unidad(es)

DEHN IBERICA Protecciones Electricas, S.A. Unipersonal · 75, C/Albasanz · ES- 28037 Madrid · Tel. +34 91 375 61 45 · www.dehn.es
 ✓ : Comprobado  Nuevo  Producto discontinuado  cross connector  parallel connector  longitudinal connector
 T connector  clamp for parallel connector  clamp for T connector  pipe clamp for parallel connector
 pipe clamp for T connector bridging component equipotential bonding bar

actualización: 06.2024

Página 1 / 1