



Presentazione

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Flush cover

Caratteristiche tecniche

Tightening Torque	Main lugs: 35 lb.in, AWG 14...AWG 10, alluminio/rame Main lugs: 45 lb.in, AWG 3, alluminio/rame Main lugs: 40 lb.in, AWG 8...AWG 4, alluminio/rame Main lugs: 35 lb.in, AWG 12...AWG10, alluminio/rame
Load Center Type	Fixed Mains (lugs)
Rated Current	70 A
Number of Spaces	2
Max Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	4
Maximum Number of Tandem Breakers	2
Number of Phases	1 fase 3 fili
Voltage Rating	120/240 V CA
Wire Size	AWG 12...AWG 3 alluminio AWG 14...AWG 4 rame
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Surface Finish	Baked enamel grigio
Box Number	2
Height	236 mm
Width	122 mm

Ambiente

Enclosure Rating	NEMA 1 indoor enclosure
Ambient Air Temperature for Operation	-5 °C 40 °C
Product Certifications	UL listed / CSA

Confezionamenti

Unità di misura confezione 1	PCE
Numero di unità per confezione 1	1
Confezione 1: altezza	10,2 cm
Confezione 1: larghezza	16,3 cm
Confezione 1: profondità	28,7 cm
Confezione 1: peso	1,68 kg

Sostenibilità dell'offerta

Stato offerta sostenibile	Prodotto Green Premium
Regolamento REACH	Dichiarazione REACH
Direttiva RoHS UE	Conforme alle esenzioni
Senza mercurio	Sì
Regolamento RoHS della Cina	Dichiarazione RoHS Della Cina
Informazioni esenzioni RoHS	Sì
Informazioni ambientali	Profilo Ambientale Del Prodotto
Profilo di circolarità	Non sono necessarie specifiche operazioni di riciclaggio

Garanzia contrattuale

Garanzia	18 months
----------	-----------